


ISO 9001  
REGISTERED**Desk-Top and Wall Plug-In Single Output Models for Europe, U.K., Australia; up to 20W**Part Number Ordering System (See Page 33)  
Input/Output Plug/Cord Options (See Page 22)**General Specifications:****Input Voltage/ Frequency:**

220VAC/230VAC/ 50Hz for Euro Type Models

**Input Voltage/ Frequency:**

240VAC 50Hz for U.K., Australia Type Models

**Output Tolerance:**

+/-5% at full load

**Protection:**

Primary Current (2) Thermal (1) Fuse

**Configuration:**

Step Down Line Transformer with Rectifier-Capacitor Input Filter, Euro./U.K./Australia (SAA) Type Wall Plug-in or Desk-Top Dual Cord In/Out

**Operating Temperature:**

0°-40°C

**Humidity:**

0%-90% R.H., non-condensing

**Storage Temperature:**

-20°-70°C

**Dielectric Strength:**4000VAC pri-sec  
1500VAC pri & sec-ground**Spacing:**

8.0mm primary-secondary

**Leakage and Patient Auxiliary Current:**

Less than 0.100mA

**Enclosure:**

Black Polycarbonate, UL94V-0

**Cooling:**

Thermal Convection, no-vents

**Cords:**Standard, 6 ft. 2 conductor, 24-18AWG Output  
For other output cords, please refer to Output Plug/Cord Options**Safety:****Medical Models Class I and Class II (BF Type):**

UR to UL 2601-1 TUV/GS to EN60601

**EMI:**

CE Compliant

**Notes:**


- 1) For unit size and output cords, please refer to Adaptors Output Plug/Cord Options
- 2) For output blade options please refer to International Adaptor Input Blade Options
- \*3) Within each Model, Output Current may vary from 50mA to Max. Load specified, in 50 mA increments, preserving Output Voltage +/-5% tolerance**

**\*\*4) Options for specifying Output Voltage Deviation from Standard Model add Suffix -x.x to Model No.****Unit Size Codes:**

- 1) Transformer Core Size:  
EI 35,4,48,57
- 2) Input Blade Style:  
Class II: 07: Euro; 09X: U.K.; 05A: Australia  
Class I: 08: Euro 3 Prong; 09A: U.K. 3 Prong; 06A: Australia 3 Prong

**Options:**

- 1) Primary earth ground PIN and secondary/shield ground
- 2) Custom output cords, connectors and shielding arrangements
- 3) Other outputs or custom design per customer specifications

**SCHEMATIC DIAGRAM:****AC Input:**220/230/240VAC  
50Hz**DC Output:**3.0VDC-48VDC  
50mA-2500mA**Model Selection Road Map Example:**

1. Required: Medical EN60601 9VDC / 700mA, EURO. "2" Prong Plug, Wall Plug-In, Output Plug Center Positive 2.5mm ID Barrel.
2. Selection table presented in increasing output voltage order; page 2: locate 9V with higher incremental current:GTM3T48-9-1000D
3. Model Selected: GTM3T48-9-700D w/ case Size EI-48; Please refer to Adaptors Case Style.
4. Output Plug/Cord selected "L-"; Please refer to Adaptors Plug/Cord Options

** MODEL NUMBER	OUTPUT (VDC)	*MAX CURRENT (MA)	CASE SIZE	DESK-TOP	EURO. WALL	U.K. WALL	SAA WALL
GTM3T35-3-600C	3.0	600	EI-35	▪	▪	▪	▪
GTM3T41-3-1300D	3.0	1300	EI-41	▪	▪	▪	▪
GTM3T48-3-1500D	3.0	1500	EI-48	▪	▪	▪	▪
GTM3T57-3-2500D	3.0	2500	EI-57	▪	▪	▪	▪
GTM3T48-3.3-1500D	3.3	1500	EI-48	▪	▪	▪	▪
GTM3T35-4-600C	4.0	600	EI-35	▪	▪	▪	▪
GTM3T41-4-1300D	4.0	1300	EI-41	▪	▪	▪	▪
GTM3T48-4-1000D	4.0	1000	EI-48	▪	▪	▪	▪
GTM3T48-4-1500D	4.0	1500	EI-48	▪	▪	▪	▪
GTM3T57-4-2300D	4.0	2300	EI-57	▪	▪	▪	▪





ISO 9001  
REGISTERED



**Desk-Top and Wall Plug-In Single Output Models for Europe, U.K., Australia; up to 20W**

Part Number Ordering System (See Page 33)  
Input/Output Plug/Cord Options (See Page 22)



FOR INDOOR USE ONLY



** MODEL NUMBER	OUTPUT (VDC)	*MAX CURRENT (MA)	CASE SIZE	DESK-TOP	EURO. WALL	U.K. WALL	SAA WALL
GTM3T48-4.5-1500D	4.5	1500	EI-48	▪	▪	▪	
GTM3T35-5-500C	5.0	500	EI-35	▪	▪	▪	▪
GTM3T41-5-1000D	5.0	1000	EI-41	▪	▪	▪	▪
GTM3T48-5-1200D	5.0	1200	EI-48	▪	▪	▪	▪
GTM3T48-5-1400D	5.0	1400	EI-48	▪	▪	▪	▪
GTM3T57-5-2300D	5.0	2300	EI-57	▪		▪	▪
GTM3T35-6-500C	6.0	500	EI-35	▪	▪	▪	▪
GTM3T41-6-900D	6.0	900	EI-41	▪	▪	▪	▪
GTM3T48-6-1200D	6.0	1200	EI-48	▪	▪	▪	▪
GTM3T48-6-1400D	6.0	1400	EI-48	▪	▪	▪	▪
GTM3T57-6-2200D	6.0	2200	EI-57	▪		▪	▪
GTM3T35-7-400C	7.0	400	EI-35	▪	▪	▪	▪
GTM3T41-7-800D	7.0	800	EI-41	▪	▪	▪	▪
GTM3T48-7-1100D	7.0	1100	EI-48	▪	▪	▪	▪
GTM3T48-7-1300D	7.0	1300	EI-48	▪	▪	▪	▪
GTM3T57-7-2000D	7.0	2000	EI-57	▪		▪	▪
GTM3T35-7.5-400C	7.5	400	EI-35	▪	▪	▪	▪
GTM3T41-7.5-800D	7.5	800	EI-41	▪	▪	▪	▪
GTM3T48-7.5-900D	7.5	900	EI-48	▪	▪	▪	▪
GTM3T48-7.5-1100D	7.5	1100	EI-48	▪	▪	▪	▪
GTM3T48-7.5-1300D	7.5	1300	EI-48	▪	▪	▪	▪
GTM3T57-7.5-2000D	7.5	2000	EI-57	▪		▪	▪
GTM3T35-9-300C	9.0	300	EI-35	▪	▪	▪	▪
GTM3T41-9-650D	9.0	650	EI-41	▪	▪	▪	▪
GTM3T48-9-1000D	9.0	1000	EI-48	▪	▪	▪	▪
GTM3T48-9-1200D	9.0	1200	EI-48	▪	▪	▪	▪
GTM3T57-9-1800D	9.0	1800	EI-57	▪		▪	▪
GTM3T48-10-700D	10.0	700	EI-48	▪	▪	▪	▪
GTM3T48-10-900D	10.0	900	EI-48	▪	▪	▪	▪
GTM3T48-10-1100D	10.0	1100	EI-48	▪	▪	▪	▪
GTM3T57-10-1500D	10.0	1500	EI-57	▪		▪	▪
GTM3T48-11-1000D	11.0	1000	EI-48	▪	▪	▪	▪
GTM3T35-12-250C	12.0	250	EI-35	▪	▪	▪	▪
GTM3T41-12-600D	12.0	600	EI-41	▪	▪	▪	▪
GTM3T48-12-800D	12.0	800	EI-48	▪	▪	▪	▪
GTM3T48-12-1200D	12.0	1200	EI-48	▪	▪	▪	▪
GTM3T57-12-1400D	12.0	1400	EI-57	▪		▪	▪
GTM3T57-12-1500D	12.0	1500	EI-57	▪		▪	▪
GTM3T48-13.5-850D	13.5	850	EI-48	▪	▪	▪	▪
GTM3T48-13.5-1000D	13.5	1000	EI-48	▪	▪	▪	▪
GTM3T35-14-200C	14.0	200	EI-35	▪	▪	▪	▪
GTM3T41-14-450D	14.0	450	EI-41	▪	▪	▪	▪

ISO 9001  
REGISTERED**Desk-Top and Wall Plug-In Single Output Models for Europe, U.K., Australia; up to 20W**Part Number Ordering System (See Page 33)  
Input/Output Plug/Cord Options (See Page 22)

FOR INDOOR USE ONLY

** MODEL NUMBER	OUTPUT (VDC)	*MAX CURRENT (MA)	CASE SIZE	DESK-TOP	EURO. WALL	U.K. WALL	SAA WALL
GTM3T48-14-500D	14.0	500	EI-48	▪	▪	▪	
GTM3T48-14-600D	14.0	600	EI-48	▪	▪	▪	▪
GTM3T48-14-800D	14.0	800	EI-48	▪	▪	▪	▪
GTM3T57-14-1300D	14.0	1300	EI-57	▪	▪	▪	▪
GTM3T35-15-200C	15.0	200	EI-35	▪	▪	▪	▪
GTM3T41-15-450D	15.0	450	EI-41	▪	▪	▪	▪
GTM3T48-15-800D	15.0	800	EI-48	▪	▪	▪	▪
GTM3T48-15-900D	15.0	900	EI-48	▪	▪	▪	▪
GTM3T57-15-1300D	15.0	1300	EI-57	▪	▪	▪	▪
GTM3T48-16-900D	16.0	900	EI-48	▪	▪	▪	▪
GTM3T57-16.5-1300D	16.5	1300	EI-57	▪	▪	▪	▪
GTM3T57-17.8-1500D	17.8	1500	EI-57	▪	▪	▪	▪
GTM3T35-18-150C	18.0	150	EI-35	▪	▪	▪	▪
GTM3T41-18-350D	18.0	350	EI-41	▪	▪	▪	▪
GTM3T48-18-350C	18.0	350	EI-48	▪	▪	▪	▪
GTM3T48-18-450D	18.0	450	EI-48	▪	▪	▪	▪
GTM3T48-18-500D	18.0	500	EI-48	▪	▪	▪	▪
GTM3T48-18-550D	18.0	550	EI-48	▪	▪	▪	▪
GTM3T48-18-700D	18.0	700	EI-48	▪	▪	▪	▪
GTM3T57-18-1100D	18.0	1100	EI-57	▪	▪	▪	▪
GTM3T48-20-500D	20.0	500	EI-48	▪	▪	▪	▪
GTM3T57-20-1000D	20.0	1000	EI-57	▪	▪	▪	▪
GTM3T35-21-150C	21.0	150	EI-35	▪	▪	▪	▪
GTM3T41-21-300D	21.0	300	EI-41	▪	▪	▪	▪
GTM3T48-21-300C	21.0	300	EI-48	▪	▪	▪	▪
GTM3T48-21-400D	21.0	400	EI-48	▪	▪	▪	▪
GTM3T48-21-500D	21.0	500	EI-48	▪	▪	▪	▪
GTM3T48-21-600D	21.0	600	EI-48	▪	▪	▪	▪
GTM3T57-21-1000D	21.0	1000	EI-57	▪	▪	▪	▪
GTM3T35-24-100C	24.0	100	EI-35	▪	▪	▪	▪
GTM3T41-24-300D	24.0	300	EI-41	▪	▪	▪	▪
GTM3T48-24-350D	24.0	350	EI-48	▪	▪	▪	▪
GTM3T48-24-450D	24.0	450	EI-48	▪	▪	▪	▪
GTM3T48-24-550D	24.0	550	EI-48	▪	▪	▪	▪
GTM3T57-24-800D	24.0	800	EI-57	▪	▪	▪	▪
GTM3T48-28-450D	28.0	450	EI-48	▪	▪	▪	▪
GTM3T57-28-700D	28.0	700	EI-57	▪	▪	▪	▪
GTM3T48-36-300D	36.0	300	EI-48	▪	▪	▪	▪
GTM3T57-36-500D	36.0	500	EI-57	▪	▪	▪	▪
GTM3T48-48-200D	48.0	200	EI-48	▪	▪	▪	▪
GTM3T57-48-350D	48.0	350	EI-57	▪	▪	▪	▪

