



ISO 9001:2000
REGISTERED



**24 Watts, Switchmode Power Supply, Single Output,
Family, Input, Medical, 11-32VDC**



ELECTRICAL SPECIFICATIONS:

INPUT VOLTAGE:
11-32 VDC

INPUT CURRENT:
<2 A (R.M.S.) MAX

OUTPUT CURRENT:
NO LOAD TO FULL LOAD, NO MINIMUM LOAD REQUIRED

OUTPUT POWER (RATED):
24 WATTS MAX

OUTPUT RIPPLE (PEAK TO PEAK):
1% TYPICAL

OUTPUT REGULATION (LINE/LOAD):
± 5 % FOR MAIN OUTPUT, MEASURED AT O/P CONNECTOR

LINE REGULATION:
± 0.5 % MAX AT FULL LOAD

TURN ON/ TURN OFF OVERSHOOT:
4% MAX 500µS MAX RECOVERY TIME FOR 25% STEP LOAD

TURN-ON DELAY:
1 SEC MAX

HOLD-UP TIME:
16 mSEC MIN AT NOMINAL INPUT AND FULL LOAD

EFFICIENCY:
75 % TYPICAL

SWITCHING FREQUENCY:
100 KHZ TYPICAL

OVER-VOLTAGE PROTECTION:
VOLTAGE LIMITED LESS 130% OF NOMINAL VOLTAGE

OVER-CURRENT / SHORT CIRCUIT:
HICCUP WITH AUTO RECOVERY TO 1.1 - 1.3 IO

OTHER PROTECTION:
INPUT FUSING

SAFETY APPROVALS:
DESIGNED TO MEET UL60601-1, CUL TO 22.2# 601, DEMKO TO EN60601-1,CE

DIELECTRIC WITHSTAND VOLTAGE:
500VAC PRIMARY-SECONDARY

LEAKAGE CURRENT:

< 0.25 mA

LINE SURGE:
EN 61000-4-5 LEVEL 4

EMI:

COMPLIES WITH EN55022 CLASS B AND FCC PART 15 CLASS B WHEN TESTED WITH A RESISTIVE LOAD, BOT CONDUCTED AND RADIATED

CE MARK:

TESTED TO COMPLY WITH EN61000-3-2 EN61000-3-3, AND EN50082-1, INCLUDING EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11, LEVEL 4. UNIT IS ELIGIBLE FOR CE MARK.

MTBF:

GREATER THAN 50,000 HOURS AT 25°C AMBIENT TEMPERATURE

OPERATING TEMPERATURE:

0°C TO 40° C

STORAGE TEMPERATURE:

-40°C TO 80° C

HUMIDITY:

0% TO 90% RELATIVE HUMIDITY

MODEL NUMBER CODE:

GTMD2: INTERNAL CODE;
1148: FAMILY ENCLOSURE DESIGNATION;

NOTES:

1. EACH OUTPUT CURRENT CAN VARY WITHIN ITS DESIGNATION RANGE., AS LONG AS THE OUTPUT POWER IS NOT EXCEEDED.
2. SINGLE OUTPUT UNITS ARE AVAILABLE FROM 3.3V UP TO 48V IN 0.1V INCREMENTS.
3. X.X.: OPTIONAL FOR SPECIFYING OUTPUT VOLTAGE DEVIATION FROM STANDARD MODEL: SUBTRACTING X.X. VOLTS FROM STANDARD OUTPUT VOLTAGE.

**OUTPUT VOLTAGE / CURRENT:
CLASS II MODELS, DOUBLE INSULATED, T2**

MODEL NUMBER	OUTPUT VOLTAGE (VDC)	OUTPUT CURRENT (A)	RATED OUTPUT POWER (W)
GTMD21148(L)-1005	+ 5.0	0 -2.0	0 - 10
GTMD21148(L)-1505	+ 5.0	0 -3.0	0 - 15
GTMD21148(L)-1507	+ 7.50	0 -2.0	0 - 15
GTMD21148(L)-2412	+ 12.0	0 -2.0	0 - 24
GTMD21148(L)-2416	+ 16.0	0 -1.5	0 - 24
GTMD21148(L)-2418	+ 18.0	0 -1.33	0 - 24
GTMD21148(L)-2424	+ 24.0	0 -1.0	0 - 24

SPECIFICATIONS MAY CHANGE WITHOUT PRIOR NOTICE. CONSULT GLOBTEK CUSTOMER SERVICE FOR LATEST SPECIFICATIONS.



ISO 9001:2000
REGISTERED



**24 Watts, Switchmode Power Supply, Single Output,
Family, Input, Medical, 11-32VDC**



ENCLOSURE: DESKTOP, DUAL CORD

HOUSING: HIGH IMPACT PLASTIC, 94VO POLYCARBONATE, NON-VENTED, COLOR BLACK



SIZE:


CLASS II MODELS:
103 X 50 X 32.5 + 1 mm

INPUT CORD:

CONDUCTOR, 18AWG (OR 20 AWG)
STRANDED WIRE, FLAT SPT-1 OR
UL2468 CORD TYPE, COLOR BLACK,
LENGTH OF THE CORD: 1830 +100,-0
mm.

CORD IS MEASURED FROM THE HOUS-
ING TO THE END OF OVERMOLD OF
THE CONNECTOR.


CABLE MARKED WITH WIRE GAUGE,
AND ALL APPLICABLE RATING AND
SAFETY APPROVALS.



INPUT CONNECTOR:


OPTION # 1:

CAR MALE CIGARETTE LIGHTER DC
POWER PLUG (+,-) TIP POSITIVE WITH
5A/125V SLO-BLO FUSE



OPTION # 2:


SPADE TONGUE TERMINAL 0.25" FAST
ON SOFT INSULATION TYPE



INPUT CONNECTOR:

OPTION # 3:

ALLIGATOR CLIPS



SPECIFICATIONS MAY CHANGE WITHOUT PRIOR NOTICE. CONSULT GLOBTEK CUSTOMER SERVICE FOR LATEST SPECIFICATIONS.



ISO 9001:2000
REGISTERED

GTMD21148 SERIES-24W



**24 Watts, Switchmode Power Supply, Single Output,
Family, Input, Medical, 11-32VDC**



ENCLOSURE: DESKTOP, DUAL CORD

HOUSING: HIGH IMPACT PLASTIC, 94VO POLYCARBONATE, NON-VENTED, COLOR BLACK



SIZE:

CLASS II MODELS:
103 X 50 X 32.5 + 1 mm


INPUT CORD:

CONDUCTOR, 18AWG (OR 20
AWG) STRANDED WIRE, FLAT
SPT-1 OR UL2468 CORD TYPE,
COLOR BLACK,

LENGTH OF THE CORD:
1830 +100,-0 mm.

CORD IS MEASURED FROM THE
HOUSING TO THE END OF OVER-
MOLD OF THE CONNECTOR.

CABLE MARKED WITH WIRE
GAUGE, AND ALL APPLICABLE
RATING AND SAFETY
APPROVALS.



INPUT CONNECTOR:

OPTION # 1:

CAR MALE CIGARETTE LIGHTER DC
POWER PLUG (+,-) TIP POSITIVE WITH
5A/125V SLO-BLO FUSE


OPTION # 2:

SPADE TONGUE TERMINAL 0.25" FAST
ON SOFT INSULATION TYPE

INPUT CONNECTOR:

OPTION # 3:

ALLIGATOR CLIPS



SPECIFICATIONS MAY CHANGE WITHOUT PRIOR NOTICE. CONSULT GLOBTEK CUSTOMER SERVICE FOR LATEST SPECIFICATIONS.

www.globtek.com

+1.201.784.1000