



ISO 9001:2000
REGISTERED



**0-15 Watts, Switchmode, Single Output, 5V@ 3A (2.2"x3.9")
Open Frame, Universal Input, ITE Class I**

Part Number Ordering System (See Page 224)



FOR INDOOR USE ONLY



ELECTRICAL SPECIFICATIONS:

INPUT VOLTAGE:
90 VAC TO 264 VAC

INPUT CURRENT:
< 0.5 A RMS AT 90 VAC INPUT

INPUT FREQUENCY:
47 HZ - 63 HZ

OUTPUT VOLTAGE:
+ 5VDC @ 0-3.0A

OUTPUT CURRENT:
NO MINIMUM LOAD REQUIRED

OUTPUT POWER (RATED):
15 WATTS MAX

OUTPUT RIPPLE (PEAK TO PEAK):
≤ 1% TYP

OUTPUT REGULATION (LINE/LOAD):
± 2 % FOR MAIN OUTPUT, MEASURED AT O/P CONNECTOR

LINE REGULATION:
± 0.5 % MAX AT FULL LOAD

ADJUSTABILITY:
+10, -5% OUTPUT VOLTAGE

REMOTE SENSING (OPTION):
PROVIDES REGULATION WITHIN ± 1% OF NOMINAL VOLTAGE OF MAIN OUTPUT AT LOAD LEVEL. FOR 3.3V SINGLE OUTPUT, REMOTE IS REQUIRED.

TURN ON/ TURN OFF OVERSHOOT:
4% MAX 500uS MAX RECOVERY TIME FOR 25% STEP LOAD

TURN-ON DELAY:
1 SEC MAX

HOLD-UP TIME:
16 m SEC MIN AT NOMINAL INPUT AND FULL LOAD

INRUSH CURRENT:
20 A MAX AT COLD START FOR N.A. (40A FOR EURO)

EFFICIENCY:
75 % TYPICAL

SWITCHING FREQUENCY:
100 KHZ TYPICAL

OVER-VOLTAGE PROTECTION:
VOLTAGE LIMITED LESS 130% OF NOMINAL VOLTAGE

OVER-CURRENT / SHORT CIRCUIT:
HICCUP WITH AUTO RECOVERY TO 1.1 - 1.3 I_O

OTHER PROTECTION:
INPUT FUSING

SAFETY APPROVALS:
UR TO UL 60950, C-UR TO 22.2 # 950, TUV TO EN 60950, CE CLASS I & II

DIELECTRIC WITHSTAND VOLTAGE:
4242VDC (3000 VAC) PRIMARY-SECONDARY;1500 VAC PRIMARY- GROUND

LEAKAGE CURRENT:
≤ 0.25 mA

LINE SURGE:
EN 61000-4-5 LEVEL 4

EMI:
COMPLIES WITH EN55022, CLASS B AND FCC PART 15 CLASS B WHEN TESTED WITH A RESISTIVE LOAD, BOTH CONDUCTED AND RADIATED

CE MARK:
TESTED TO COMPLY WITH EN61000-3-2 EN61000-3-3, AND EN50082-1, INCLUDING EN61000-4-2 (SYSTEM LEVEL), EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11, LEVEL 4.

MTBF:
GREATER THAN 200,000 HOURS AT 25°C AMBIENT TEMPERATURE

OPERATING TEMPERATURE:
0° C TO 40° C

STORAGE TEMPERATURE:
-40° C TO 80° C

HUMIDITY:
0% TO 90% RELATIVE HUMIDITY

OUTPUT VOLTAGE / CURRENT:

MODEL NUMBER	OUTPUT VOLTAGE (VDC)	OUTPUT CURRENT (mA)	RATED OUTPUT POWER (W)
GT-21098-1505	+ 5.0	0 - 3.0	0 - 15

SPECIFICATIONS MAY CHANGE WITHOUT PRIOR NOTICE. CONSULT GLOBTEK CUSTOMER SERVICE FOR LATEST SPECIFICATIONS.



**0-15 Watts, Switchmode, Single Output, 5V@ 3A (2.2"x3.9")
Open Frame, Universal Input, ITE Class I**

Part Number Ordering System (See Page 224)


MECHANICAL CONFIGURATION:

INPUT CONNECTOR:

SQUARE PIN LOCKING HEADERS, WITH .312(7.92) BETWEEN CONDUCTORS, .045 (1.14) SQUARE PINS, TIN PLATED UL 94V-0 RATED NYLON HOUSING, MOLEX: 09-65-2038 (3 CIRCUITS, WITH 1 PIN REMOVED FOR CLASS II). HEADER MATES WITH MOLEX NO. 2139 CONNECTOR OR EQUIVALENTS.

OUTPUT CONNECTOR:

OPEN FRAME: 4 PIN STRAIGHT SQUARE PIN FULLY SHROUDED HEADER, MOLEX: 35312-0410 UL 94V-0 RATED NYLON HOUSING; .098(2.50) PITCH BETWEEN CONDUCTORS, .025(.64) SQUARE PINS, TIN PLATED, HEADER MATCH WITH MOLEX # 35155 CONNECTORS OR EQUIVALENT.



OPTION:

10 MIL 94V-0 FIBER GLASS (2.17 X 3.90) INCH, W/4HOLES MATCHING MOUNTING HOLE POSITIONS, TERMINAL BOARD WITH RTV UNDERNEATH THE POWER PC BOARD IN 6 PLACES.

