

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-21096-WWVV-F

May 4, 2024

GT-21096-WWVV-F

Information

Model Number	GT-21096-WWVV-F
Description	GT-21096-WWVV-F, ICT/ITE Power Supply, Open Frame/Internal, Regulated Switchmode AC-DC Power Supply AC Adaptor, , Input Rating: 100-240V~, 50-60 Hz, Molex 09-65-2058 5 Position Header Pin 1: Earth, Pin 2: Removed, PIN 3: Neutral, Pin 4: removed, Pin 5: Line, Output Rating: 19 Watts, Power rating with convection cooling (W) , 3.3-48V in 0.1V increments, Approvals: UKCA; CB 62368 (pending); CB 62368 (pending); CB 60950; Designed to meet EN 60601-1; WEEE; RoHS; China RoHS; VCCI; cRUus; CE; EAC; Ukraine; Class I; SIQ;
Model Picture	
Agency Documents	http://www.globtek.info/certs/GT-21096/
CE EC-Declaration	https://www.globtek.com/pdf/ec_declaration/a0O30000007P7Z7EAK
RoHS/RoHS2 Declaration	https://www.globtek.com/pdf/rohs_cert/a0O30000007P7Z7EAK
REACH Declaration	https://www.globtek.com/pdf/iso_certificates/REACH.pdf
Conflict Minerals Declaration	https://www.globtek.com/pdf/conflict-minerals.pdf

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-21096-WWVV-F

May 4, 2024

MODEL PARAMETERS


Type	Open Frame/Internal
Technology	Regulated Switchmode AC-DC Power Supply AC Adaptor
Category	ICT/ITE Power Supply
Input Voltage	100-240V~, 50-60 Hz
I/P Amps (A)	0.5A MAX
Wattage (W)	19.0
Vout Range (V)	3.3-48
Efficiency Level	N/A
Ingress Protection	IPX0
Size (mm)	

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-21096-WWVV-F

May 4, 2024

ENCLOSURE



IF PRODUCT GROUNDING IS SPECIFIED AS E1 THE LOCATION C12 IS A JUMPER
 IF PRODUCT GROUNDING IS SPECIFIED AS F3 THE LOCATION C12 IS A CAPACITOR

FOR PROPER GROUNDING RELIABILITY USE THE OPTIONAL JUMPER WIRE BELOW BETWEEN HOLES 3 AND 4



RING TERMINAL, AMP P/N: 8-34142-5 AWG 18 STRANDED WIRE, GREEN, 100 mm LENGTH

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-21096-WWVV-F

May 4, 2024

RATING TABLE

Model Number	Voltage	Amps(A)	Watts(W)	RFQ
GT-21096-0903-F	3.3 V	2.6	8.58	RFQ
GT-21096-1505-F	5 V	2.6	13.00	RFQ
GT-21096-1305-F	5 V	2.6	13.00	RFQ
GT-21096-1506-F	6 V	2.5	15.00	RFQ
GT-21096-1509-1.5-F	7.5 V	2	15.00	RFQ
GT-21096-1509-F	9 V	1.7	15.30	RFQ
GT-21096-1512-F	12 V	1.25	15.00	RFQ
GT-21096-1815-F	15 V	1.2	18.00	RFQ
GT-21096-1818-F	18 V	1	18.00	RFQ
GT-21096-1824-F	24 V	0.75	18.00	RFQ
GT-21096-1948-F	48 V	0.4	19.20	RFQ

Model:GT-21096-WWVV-F

May 4, 2024

SPECIFICATIONS

A) ELECTRICAL SPECIFICATIONS:

01. Input Voltage: Specified 90-264 Vac, Nameplate rated: 100-240Vac
02. Input Frequency: Specified 47-63 Hz, Nameplate rated 50-60Hz
03. Output Regulation: +/- 5% measured at the output connector
04. Line Voltage Regulation: +/- 1% typical measured at full load
05. Output Ripple (Vp-p): +/- 1% of output voltage, Vp-p, typical
06. Turn-ON/OFF: 5% maximum, 1 mS typical recovery time for 25% step load
07. Turn-ON Delay: 1 Sec, typical
08. Hold-Up Time: 8 mS typical @ nominal input voltage and full load
09. Inrush Current: 30A maximum cold start @ 115 Vac input, 60A maximum cold start @ 230 Vac input
10. Switching Frequency: 100 KHz typical, varies with line and load
11. Efficiency: 75% typical at nominal input and full load

B) PROTECTION

01. Over-Voltage: limited via crowbar method
02. Earth Leakage Current: <3.5 mA at 240Vac input voltage
03. Short Circuit/Over-load: momentary short circuit protected, output will autorecover upon removal of short
04. Input Protection: Input line fusing

C) SAFETY

01. Dielectric Withstand Voltage: 4242 Vdc from primary to secondary
02. Touch Current: <0.25mA at 240 Vac input voltage
03. Earth continuity test:<0.1 Ohm or < 0.2 Ohm when with a non-detachable Power Supply cord for E1 configuration
04. Type of protection against electric shock: class I for E1 configuration
05. Degree of protection against electric shock: not classified(no applied part)
06. Mode of operation: Continuous
07. ROHS 2: Complies with EU 2011/65/EU and China SJ/T 11363-2006

D) OTHER:

01. MTBF: 200,000 Hours @ 25°C ambient temperature
02. Operating Temperature: 0°C to 40°C ambient temperature
03. Humidity: 0% to 90% relative humidity
04. Storage Temperature: -10°C to 80°C
05. Cooling: Convection


E) ENCLOSURE

01. Housing: Open Frame
02. Size: 84.6 x 41.5 x 28.9 mm

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-21096-WWVV-F

May 4, 2024



PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.


<https://www.globtek.com/ds/dakCoNGHVxv/rqfMaHc9ZAm.html>

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-21096-WWVV-F

May 4, 2024

DERATING CURVE



Model:GT-21096-WWVV-F




May 4, 2024

INPUT CONFIGURATION

Description Molex 09-65-2058 5 Position Header Pin 1: Earth, Pin 2: Removed, PIN 3: Neutral, Pin 4: removed, Pin 5: Line

Document: http://www.molex.com/pdm_docs/sd/009652058_sd.pdf

Catalog Page: http://www.molex.com/molex/products/datasheet.jsp?part=active/0009652058_PCB_HEADERS.xml



Mates With Part(s):

5195 SPOX™ Crimp Housing, **5239** KK® Crimp Housing

Model:GT-21096-WWVV-F

May 4, 2024

Approvals

Logo	Description
	Attention Mark / Refer to operating manual for operating and service instructions
No Logo	CB Certificate IEC 60950-1:2005 (2nd Edition), Am 1: 2009, CB report IEC 60950-1:2005 (2nd Edition), Am 1: 2009 and EN 60950-1:2006 + Am 1:2010 + Am 11:2009 + Am 12:2011
No Logo Applicable	CB for IEC 62368-1:2014 (Second Edition)
No Logo Applicable	CB for IEC 62368-1:2014 (Second Edition) (pending)
	CE Certification
	CHINA SJ/T 11364-2014, China RoHS Chart: http://www.globtek.com/pdf/F-GT-DJD-8.4.1-006%20China%20RoHS%20Declaration%205-20-22.pdf
	Class I Earth Ground
	cRUus Registered E170507 CSA C22.2 No. 60950-1-03 1st Ed.
No Logo	Designed to meet EN 60601-1:2006 + A11:2011 +A1:2013 3rd Edition
	Declaration ДС № EAЭC N RU Д-US.KA01.B.10453_19 Custom Union of Russia, Belarus and Kazakhstan http://www.globtek.com/redirect/?loc=gost-certificate-eac-declaration
	Indoor Use Only - Mark is on the label or Molded in the case
RoHS	Specifications of directive 2011/65/EU Annex VI (ROHS-2) with amendment 2015/863-EU (ROHS-3) http://www.ce-mark.com/Rohs%20final.pdf

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-21096-WWVV-F

May 4, 2024

	SIQ Mark EN 60950-1 :2006 +A 1 :2010 +A 11 :2009 +A 12:2011 + A2:2013
	UKCA Certification
	Ukraine UKRSePro (Document: www.globtek.com/html/iso_certificates/GT_Ukraine.pdf)
	Japan: Voluntary Control Council for Interference (VCCI)
	WEEE: Complies with EU 2012/19/EU (http://ec.europa.eu/environment/waste/weee/index_en.htm) Mark is on the label or Molded in the case