

http://www.globtek.com/iso-certificates.php

Delivering leading edge, innovative power solutions for more than 30 years....

# Model:Battery18650G May 5, 2024 Battery18650G Information Model Number Battery18650G Battery18650G, , Battery Cylindrical Can, Battery Li-Ion, , Input Rating: , , Output Rating: Watts, Power rating with convecti Description V in 0.1V increments, Approvals: Model Picture For Representation Only Agency http://www.globtek.info/certs/BL2600C186503S1PGXG%20GS-1907%20UN38.3%20Battery%20(11.1-12.6V%202600mA Documents CF EC-Declaration RoHS/RoHS2 https://www.globtek.com/pdf/rohs\_cert/a0Oa000000FiDk9EAF Declaration REACH https://www.globtek.com/pdf/iso\_certificates/REACH.pdf Declaration Conflict Minerals https://www.globtek.com/pdf/conflict-minerals.pdf Declaration



http://www.globtek.com/iso-certificates.php

Delivering leading edge, innovative power solutions for more than 30 years....

#### Model:Battery18650G

May 5, 2024

MODEL PARAMETERS	
Туре	Battery Cylindrical Can
Technology	Battery Li-Ion
Category	
Input Voltage	
I/P Amps (A)	
Wattage (W)	
Vout Range (V)	
Efficiency Level	
Ingress Protection	
Size (mm)	



http://www.globtek.com/iso-certificates.php

May 5, 2024

Delivering leading edge, innovative power solutions for more than 30 years....

Model:Battery18650G

### ENCLOSURE





"Your power partner" http://www.globtek.com/iso-certificates.php

Delivering leading edge, innovative power solutions for more than 30 years....

ATING TABLE					
lodel Number	Voltage	Amps(A)	Watts(W)	RFQ	



http://www.globtek.com/iso-certificates.php

Delivering leading edge, innovative power solutions for more than 30 years....

Model:Battery18650G SPECIFICATIONS Cell Specifications: Manufacturer: Globtek Part Number: Cylindrical 18650 01) Rated Capacity: 2.60 Ah Typical, 2.50 Ah minimum 02) Nominal Voltage: 3.7V 03) Watt-Hour rating: 9.62 Watt Hour 04) Ambient Temperature During Charging: 0°C to +40°C 05) Ambient Temperature During Discharging: -20°C to +60°C 06) Size 65.2H818.6D mm 07) Humidity: 65 +/- 20% Relative Humidity 08) Storage Temperature and Charge Retention: 1 Year at -20C to +20C; >80% 3 Months at -20C to +45C; >80% 1 Month at -20C to +60C; >80% 09) Cells Approved to : UL1642 10) RoHS: Complies with EU 2002/95/EC and China SJ/T 11363-2006 11) Transportation: Designed to meet UN 38.3 12) Warranty: 5 years warranty on the battery pack excluding the cells themselves which are covered by the Manufacturer's original warranty at their published warranty period. Please refer to the manufacturer's warranty policy for cells.

May 5, 2024



http://www.globtek.com/iso-certificates.php

Delivering leading edge, innovative power solutions for more than 30 years....

Model:Battery18650G

## **DERATING CURVE**





May 5, 2024



http://www.globtek.com/iso-certificates.php

Delivering leading edge, innovative power solutions for more than 30 years....

Model:Battery18650G

INPUT CONFIGURATION





http://www.globtek.com/iso-certificates.php

"Your power partner"

Delivering leading edge, innovative power solutions for more than 30 years....

#### Model:Battery18650G

May 5, 2024

# Approvals Logo