

Delivering leading edge, innovative power solutions for more than 30 years....

Model:DA-19.2-24G

May 6, 2024

## DA-19.2-24G

### Information

Model Number	DA-19.2-24G
Description	DA-19.2-24G, ICT/ITE Power Supply, Wall Plug-in, Regulated Linear AC-DC Power Supply AC Adaptor, , Input Rating: 115V~ / 60Hz, North America Blades with Ground Prong, Class I, (3) Conductors, Output Rating: 23.6 Watts, Power rating with convection cooling (W) , 24V in 0.1V increments, Approvals:
Model Picture	
Agency Documents	
CE EC-Declaration	<a href="https://www.globtek.com/pdf/ec_declaration/a0Oa000000FjHdvEAF">https://www.globtek.com/pdf/ec_declaration/a0Oa000000FjHdvEAF</a>
RoHS/RoHS2 Declaration	<a href="https://www.globtek.com/pdf/rohs_cert/a0Oa000000FjHdvEAF">https://www.globtek.com/pdf/rohs_cert/a0Oa000000FjHdvEAF</a>
REACH Declaration	<a href="https://www.globtek.com/pdf/iso_certificates/REACH.pdf">https://www.globtek.com/pdf/iso_certificates/REACH.pdf</a>
Conflict Minerals Declaration	<a href="https://www.globtek.com/pdf/conflict-minerals.pdf">https://www.globtek.com/pdf/conflict-minerals.pdf</a>

Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

May 6, 2024

**MODEL PARAMETERS**

Type	Wall Plug-in
Technology	Regulated Linear AC-DC Power Supply AC Adaptor
Category	ICT/ITE Power Supply
Input Voltage	115V~ / 60Hz
I/P Amps (A)	
Wattage (W)	23.6
Vout Range (V)	24
Efficiency Level	USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782
Ingress Protection	
Size (mm)	

**PROPRIETARY INFORMATION**

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

[n/a](#)

Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

May 6, 2024

ENCLOSURE

---

Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

May 6, 2024

## RATING TABLE

Model Number	Voltage	Amps(A)	Watts(W)	RFQ
DA-16.2-15D-EI48	15 V	1	15.00	<a href="#">RFQ</a>
DA-19.2-24G	24 V	0.8	19.20	<a href="#">RFQ</a>

## PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED  
EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.[n/a](#)

Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

May 6, 2024

## SPECIFICATIONS

Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

May 6, 2024

## DERATING CURVE

---

Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

May 6, 2024

**INPUT CONFIGURATION**

Description	North America Blades with Ground Prong, Class I, (3) Conductors
-------------	---

**PROPRIETARY INFORMATION**

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

[n/a](#)

Model:DA-19.2-24G

May 6, 2024

## OUTPUT CONFIGURATION

Common output connector options:



L Type (Coaxial  
5.5x2.5mm plug)



C Type (Coaxial  
5.5x2.1mm plug)



K Type (Coaxial  
3.5x1.3mm plug)



LL Type (5.5x2.5mm  
Locking 760k type)



CL Type (5.5x2.1mm  
Locking S761k type)



ML2 Type (Molex  
housing 43025-0200)



YL3 Type  
(KPPX-3P)



YL4 Type (KPPX-4P)



EJ1/2/3/4/5 (EIAJ  
RC-5320A type  
connectors)



MSB Type (Micro  
USB)



USBC Type (USB  
Type C)



Inquire for custom  
design

For a comprehensive list of options, [click here](#)

Contact GlobTek for your specific requirements or custom solutions.



Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

May 6, 2024

## Approvals

Logo	
------	--