

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GTM41060-WWVV-Q-IM

May 6, 2024

GTM41060-WWVV-Q-IM

Information

Model Number

GTM41060-WWVV-Q-IM

Description

GTM41060-WWVV-Q-IM, ICT / ITE / Medical Power Supply, 60601-1-4th Ed. , Wall Plug-in, Regulated Switchmode AC-DC Power Supply AC Adaptor, , Input Rating: 100-240V~, 50-60 Hz, Blade Options for Q Series Wall Plug-in Power Supplies, Output Rating: 25 Watts, Power rating with convection cooling (W) , 3.0-30V in 0.1V increments, Approvals: cUR (up to 30V only); Belarus (12V only); EAC; RCM; UKCA; CE; Book 60601; CB 60601-1; CE; CE; China RoHS; Israel (5V only); cUR; Double Insulation; FCC; IP52; Level IV 1meter 115; NrCAN; PSE; RoHS; SIQ (up to 30V only); Ukraine; VCCI; WEEE; Taiwan BSMI (12V only); CB 60950; CCC; cULus; IRAM; Korea (12V Only); LPS (9V-30V); PSE; 2MOPP;

Model Picture



Agency Documents

<http://www.globtek.info/certs/GTM41060/>

CE EC-Declaration

https://www.globtek.com/pdf/ec_declaration/a00a000000Mi5pJEAR

RoHS/RoHS2 Declaration

https://www.globtek.com/pdf/rohs_cert/a00a000000Mi5pJEAR

REACH Declaration

https://www.globtek.com/pdf/iso_certificates/REACH.pdf

Conflict Minerals Declaration

<https://www.globtek.com/pdf/conflict-minerals.pdf>

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GTM41060-WWVV-Q-IM

May 6, 2024

MODEL PARAMETERS


Type	Wall Plug-in
Technology	Regulated Switchmode AC-DC Power Supply AC Adaptor
Category	ICT / ITE / Medical Power Supply
Input Voltage	100-240V~, 50-60 Hz
I/P Amps (A)	0.6 A
Wattage (W)	25.0
Vout Range (V)	3.0-30
Efficiency Level	IV
Ingress Protection	IP40
Size (mm)	

Delivering leading edge, innovative power solutions for more than 30 years....

Model: GTM41060-WWVV-Q-IM

May 6, 2024

ENCLOSURE



Delivering leading edge, innovative power solutions for more than **30** years....

Model:GTM41060-WWVV-Q-IM

May 6, 2024

RATING TABLE

Model Number	Voltage	Amps(A)	Watts(W)	RFQ
GTM41060-2512-IM	12 V	2.08	24.96	RFQ
GTM41060-2515-IM	15 V	1.67	25.05	RFQ

Model:GTM41060-WWVV-Q-IM

May 6, 2024

SPECIFICATIONS

A) ELECTRICAL SPECIFICATIONS:

01. Input Voltage: Specified 90-264 Vac, Nameplate rated: 100-240Vac
02. Input Frequency: Specified 47-63 Hz, Nameplate rated 50-60Hz
03. Output Regulation: +/- 5% of nominal output voltage
04. Line Voltage Regulation: +/- 1% maximum at full load
05. Output Ripple (Vp-p): 1% or 150 mV whichever is greater measured at 20 MHz bandwidth with 0.1 uf ceramic capacitor in parallel with 10 uf electrolytic capacitor connected at the end of output connector at nominal line
06. Turn-On/Turn-Off Overshoot: 5% maximum, 500uS maximum recovery time for 25% to 50% step load
07. Turn-On Delay: 3000mSEC maximum at full load, 115VAC
08. Hold-Up Time: 10mS minimum at nominal input and full load
09. Inrush Current: 30A maximum at cold start 120VAC and 60A maximum cold start at 230 VAC
10. Switching Frequency: 66.5 KHz typical
11. Current Limited Option: Models numbers containing CC are "Current Limited" to rated output current with a tolerance of +/-10%

B) PROTECTION

1. Over-Voltage: Protected, unit will recover upon removal of fault
2. Over-Load: Protected, unit will recover upon removal of fault
3. Short Circuit: Protected, unit will recover upon removal of fault
4. No load power consumption: Meet Energy Star level IV, 115Vac
5. Input Protection: Input line fusing

C) SAFETY

1. Dielectric Withstand Voltage: 5656Vdc from primary to secondary
2. Earth Leakage Current: N/A for Class II units, there is no PE Ground pin, so Earth Leakage current is not measured
3. Touch Current: Maximum allowed values: 100uA NC(Normal condition) 500uA SFC(single fault condition)
4. Means of Protection: 2MOPP

D) OTHER:

1. MTBF: 200,000 hours @ 25°C ambient temperature
2. Operating Temperature: 0°C to 40°C ambient temperature
Optional Operating Temperature: -5°C to 40°C ambient temperature (RFP4385)
3. Humidity: 0% to 90% relative humidity
4. Storage Temperature: -10°C to 80°C
5. ROHS 2: Complies with EU 2011/65/EU and China SJ/T 11363-2006
6. Ingress protection(employed)(not employed): IP52 to IEC60529:2001 Protected against dust - limited ingress (no harmful deposit) and Protected against direct sprays up to 15o from the vertical

E) ENCLOSURE

1. Upper Housing: High impact plastic, 94V0 polycarbonate, non-vented
2. Lower Housing: High impact plastic, 94V0 polycarbonate, non-vented
3. Size: 84.0* 56.0*37.9 mm +/-1.0
4. Green LED indicator for power "Power On"

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

<https://www.globtek.com/ds/X6XYmcFvyje/nkyyqT9odRo.html>

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GTM41060-WVVV-Q-IM

May 6, 2024

DERATING CURVE

Model:GTM41060-WWVV-Q-IM


May 6, 2024

INPUT CONFIGURATION

Description Blade Options for Q Series Wall Plug-in Power Supplies

Data Sheet: <http://en.globtek.com/interchangeable-blades.php>

Insertion Instructions: <http://www.globtek.com/pdf/Instructions-Interchangeable-Blades.pdf>

Video: [Q-Blade Style Instruction Video](#)


INPUT CONNECTOR: Q-Socket (below are available blades configurations which are "not included" (unless stated above); can be purchased separately, package with power supply or as a separate "Q-KIT" if specified

01. United States / Canada / Japan NEMA 1-15P/ IEC PLUG Type A [WORKS IN PLUG B] configuration: NA 2 blades, Class II; US/CA/JP P/N: Q-NA(R)
02. Australian AS 3112 configuration: SAA 2 blade/ IEC TYPE I, Class II; AU P/N: Q-SAA(R)
03. UK BS 1363 configuration: UK 3 blade with dummy Ground/ IEC TYPE G, Class II; GB P/N: Q-UK(R)
04. European CEE 7/16 configuration: Europlug 2 pins/ IEC TYPE C [WORKS IN TYPE E&F], Class II; EU P/N: Q-EU(R)
05. Korean KS C8305 configuration: 2 pins/SIMILAR TO IEC TYPE C, Class II; KR P/N: Q-KR(R)
06. Argentina IRAM 2073 configuration: 2 blades/SIMILAR TO IEC TYPE I; AR P/N: Class II Q-AR(R)
07. China GB 2099 configuration: 2 blades/SIMILAR TO TYPE A, Class II; CN P/N: Q-CN(R)
08. India IS 1293 6A/BS546 configuration: 5A, 3 pins with Dummy Ground, Class II/IEC TYPE D; IN P/N: Q-IN(R)
09. IEC60320/C18 Inlet, Class II; P/N: Q-C18(R)
10. Brazilian NBR6147 configuration: 2 pins, Class II;SIMILAR TO IEC TYPE C BR P/N: Q-BR(R)
11. South Africa SABS164-1 and India IS 1293, IS694, 16A type plug, 3 round prongs, Class II + dummy ground, IEC TYPE M P/N: Q-SANS164-1-16A(R)
12. South Africa SABS164-4, 3 round prongs with a notched prong @ 0°, Class II + dummy ground, IEC TYPE M Red, P/N: Q-SANS164-4C-16A(R)

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

<https://www.globtek.com/ds/X6XYmcFvyJe/nkyqT9odRo.html>

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GTM41060-WWVV-Q-IM

May 6, 2024

13. South Africa SABS164-4, 3 round prongs with a notched prong @ -53°, Class II + dummy ground, Blue, IEC TYPE M,
P/N:

Q-SANS164-4L-16A(R)

14. South Africa SABS164-4, 3 round prongs with a notched prong @ +53°, Class II + dummy ground, Black, IEC TYPE M
P/N:

Q-SANS164-4R-16A(R)

Kits

01. Q-KIT: 1,2,3,4 above

02. Q-KIT-INTL: 2,3,4 above

03. Q-KIT-6: 1,2,3,4,5,6 above

04. Q-KIT-7: 1,2,3,4,5,6,7 above

05. Q-KIT-8: 1,2,3,4,5,6,7,8 above

Delivering leading edge, innovative power solutions for more than 30 years....

Model: GTM41060-WWVV-Q-IM

May 6, 2024

OUTPUT CONFIGURATION

Common output connector options:



L Type (Coaxial
5.5x2.5mm plug)



C Type (Coaxial
5.5x2.1mm plug)



K Type (Coaxial
3.5x1.3mm plug)



LL Type (5.5x2.5mm
Locking 760k type)



CL Type (5.5x2.1mm
Locking S761k type)



ML2 Type (Molex
housing 43025-0200)



YL3 Type
(KPPX-3P)



YL4 Type (KPPX-4P)



EJ1/2/3/4/5 (EIAJ
RC-5320A type
connectors)



MSB Type (Micro
USB)



USBC Type (USB
Type C)



Inquire for custom
design

For a comprehensive list of options, [click here](#)

Contact GlobTek for your specific requirements or custom solutions.

Delivering leading edge, innovative power solutions for more than 30 years....

Model: GTM41060-WWVV-Q-IM

May 6, 2024

Approvals

Logo	Description
2MOPP	2 x MOPP (Means of Patient Protection) marked with 2MOPP near model name
	Belarus certificate JII By/I 12 03. 1 I . 020 05936 only for GTM41060-2512 and GT-41060-2512
	60601-1 3rd Operating Instructions
 R32282 RoHS (Pb)	Taiwan BSMI (12V designs only); http://www.bsmi.gov.tw/wSite/ct?xItem=4072&ctN
No Logo Applicable	CB report IEC 60601-1: 2005 + CORR. 1 (2006) + CORR. 2 (2007) and or EN 60601-1:2012 Edition including 2MOOP requirements
No Logo Applicable	CB report 60950-1 2nd Ed
	CCC to GB4943.1-2011; GB/T9254-2008 GB17625.1-2012, Tropical <2000
	CE Certification CE Mark: tested to comply with EN 55032:2012+AC:2013 EN 61000-3-2:2014 EN 61000-3-3:2014 EN 60601-1-2:2015 EN 55024:2010
	CE Mark: tested to comply with EN55022:2006/A1:2007 Class B, EN610003-2, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6N EMI: Complies with EN55011 CLASS B and FCC Part 15B - On label or Molded in case
	CE Mark: tested to comply with EN 60601-1-2:2015 Medical electrical equipment Part 1 on the label or Molded in the case

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

<https://www.globtek.com/ds/X6XYmcFvyJe/nkyqT9odRo.html>

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GTM41060-WWVV-Q-IM

May 6, 2024

	CHINA SJ/T 11364-2014, China RoHS Chart: http://www.globtek.com/pdf/F-GT-DJD-8.4.1-006%20China%20RoHS%20Declaration
	ANSI/AAMI ES60601-1: A1:2012, C1:2009/(R)2012 and A2:2010/(R)2012, CSA CANO. 60601-1:14 up to 30V only
	UL60950-1, cULus to UL 60950-1, 2nd Edition, 2007-03-27 and CSA C22.2 No. 60950-1, 2nd Edition, 2007-03
	UR 60601-1, 3rd Edition, CAN/CSA-C22.2 No. 601.1-1
	
	Certification # TC RU 0585806 Custom Union of Russia, Belarus and Kazakhstan
	FCC PART 15 CLASS B
	Indoor Use Only - Mark is on the label or Molded in the case
IP52	Ingress Protection: ?IP52 to IEC60529:2001 Protected against dust - limited ingress deposit) and Protected against direct sprays up to 15 degrees from the vertical
 DC-E-G71-002.1 PRECAUCION: PARA USO EN EQUIPOS ELECTRONICOS SOLAMENTE	IRAM certificate DC-E-G71-002.1 to IEC 60950 + A1:2009
ITE כוח קפץ	Electromagnetic compatibility of ME EQUIPMENT and ME SYSTEMS Of Israel Standard SI 60061 Part 1 – Medical equipment: General requirements for essential performance, Mar. 2008. (5 Volts Only)
	JAPAN TUV R-PSE, Cert. No. JD 50314327, to J60950-1(H26) , J55022(H22),J300

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GTM41060-WWVV-Q-IM

May 6, 2024

 GlobTek, Inc.	[15V?30V]. Please reference the following website for guidelines on PSE regulations https://www.globtek.com/r2/Szj4Vb
 GlobTek, Inc.	JAPAN TUV R-PSE, Cert. No. JD 50314327, to J60950-1(H26) , J55022(H22),J300 less]. Please reference the following website for guidelines on PSE regulations: https://www.globtek.com/r2/Szj4Vb
 Mfr. Name: GLOBTEK (SUZHOU) CO.,LTD A/S Center: 10-6221-6100	Korea KET KC Mark GT-41060-2512 HU10173-10024A (12V Only)
EFFICIENCY LEVEL  115V	Efficiency: complies to section 301 of Energy Independence and Security Act (EISA) Energy Star tier 2 (North America), ECP tier 2 (China), MEPS tier 2 (Australia), Code (Europe) exception 5.1~6.9V require 1000 mm output cable
LPS	Limited Power Source GT-41060 9 - 30 volts only
 EEV1191	Natural Resources Canada (NRCAN): CSA Standard C381.1-08, QSP NRCAN EEV http://shop.csa.ca/en/canada/energy-efficiency/canicsa-c3811-08/inv/27024802008
	Australia and New Zealand Regulatory Compliance, Mark (http://rcm.standards.org.au/rcmfaq/rcmfaq.htm) (pending)
RoHS	Specifications of directive 2011/65/EU Annex VI (ROHS-2) with amendment 2015/86 http://www.ce-mark.com/Rohs%20final.pdf
	IEC 60601-1:2005 (Third Edition) + CORR. 1:2006 + CORR. 2:2007 + A1:2012 (or IEC 60601-1: 2012 reprint) up to 30V only
	UKCA Certification
 10276	Ukraine UKRSepro (Document: www.globtek.com/html/iso_certificates/GT_Ukraine.)

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GTM41060-WWVV-Q-IM

May 6, 2024

	Japan: Voluntary Control Council for Interference (VCCI)
	WEEE: Complies with EU 2012/19/EU (http://ec.europa.eu/environment/waste/weee) Mark is on the label or Molded in the case