


Ni-Cd batteries and battery packs

Part numbering system

- Number of cells in a pack
- Battery type
- Battery capacity
- Ni-MH Battery
- Configuration code
- Connector Code:
M(MITSUM-M63)
X(MOLEX-5264-02)
W(WIRE)
- Black Wire Place or Wire Awg.



J(JST-EHR-02)
U(UNIVERSAL)
T(Tab)

Type	Model No.	Nominal Voltage(V)	Nominal Capacity (mAh)	Dimension		Standard Charge		Rapid Charge		Weight Approx. (g)
				Diameter (mm)	Height (mm)	Current (ma)	Time(h)	Current (mA)	Time(h)	
	GT-2/3AAA18	1.2	180	10.0±0.5	28.5±0.5	18	16	180	1.5	6
	GT-AAA30	1.2	300	10.0±0.5	44.0±0.5	30		300	1.5	11
	GT-5/4AAAA40	1.2	400	10.0±0.5	50.0±0.5	40		400	1.5	13
	GT-1/3AA18	1.2	180	14.0±0.5	16.0±0.5	18		180	1.5	8
	GT-2/3AA30	1.2	300	14.0±0.5	28.0±0.5	30		300	1.5	13
	GT-2/3AA40	1.2	400	14.0±0.5	28.0±0.5	40		400	1.5	14
	GT-4/5AA70	1.2	700	14.0±0.5	43.5±0.5	70		700	1.5	20
	GT-AA60J	1.2	600	14.0±0.5	49.5±0.5	60		600	1.5	22
	GT-AA80	1.2	600	14.0±0.5	48.0±0.5	60		600	1.5	22
	GT-AA70J	1.2	700	14.0±0.5	49.5±0.5	70		700	1.5	23
	GT-AA70	1.2	700	14.0±0.5	48.0±0.5	70		700	1.5	23
	GT-AA80J	1.2	800	14.0±0.5	49.5±0.5	80		800	1.5	23
	GT-AA80	1.2	800	14.0±0.5	48.0±0.5	80		800	1.5	23
	GT-AA90J	1.2	900	14.0±0.5	49.5±0.5	90		900	1.5	24
GT-4/3AA110	1.2	1100	14.0±0.5	65.0±0.5	110	1100		1.5	29	
	GT-2/3A60	1.2	600	16.5±0.5	27.5±0.5	60		600	1.5	18
	GT-2/3A70	1.2	700	16.5±0.5	27.5±0.5	70	700	1.5	18	
	GT-4.5A120	1.2	1200	16.5±0.5	42.5±0.5	120	1200	1.5	27	
	GT-A140	1.2	1400	16.5±0.5	48.5±0.5	140	1400	1.5	32	
	GT-4/5SC100P	1.2	1000	22.5±0.5	34.0±0.5	100	1000	1.5	40	
	GT-SC130P	1.2	1300	22.5±0.5	42.5±0.5	130	1300	1.5	47	
	GT-SC150P	1.2	1500	22.5±0.5	42.5±0.5	150	1500	1.5	48	
	GT-SC130	1.2	1300	22.5±0.5	42.5±0.5	130	1300	1.5	47	
	GT-SC180	1.2	1800	22.5±0.5	42.5±0.5	180	1800	1.5	49	
	GT-2/3C100	1.2	1000	25.0±0.5	30.5±0.5	100	1000	1.5	46	
	GT-C250	1.2	2500	25.5±0.5	49.3±0.5	250	2500	1.5	75	
	GT-D400	1.2	4000	32.5±0.5	60.0±0.5	400	4000	1.5	140	
	GT-D450	1.2	4500	32.5±0.5	60.0±0.5	450	4500	1.5	145	
	GT-AA60T	1.2	600	14.0±0.5	48.0±0.5	30	24	600	1.5	23
	GT-C200T	1.2	2000	25.5±0.5	49.3±0.5	100		2000	1.5	72
	GT-D400T	1.2	4000	32.5±0.5	60.0±0.5	200		4000	1.5	140