

Ni-MH batteries and battery packs

Part numbering system

1. Number of cells in a pack
2. Battery type
3. Battery capacity
4. Ni-MH Battery
5. Configuration code
6. Connector Code:
M(MITSUM-M63)
X(MOLEX-5264-02)
W(WIRE)
T(Tab)
7. Black Wire Place or Wire Awg.



Type	Model No.	Nominal Voltage(V)	Nominal Capacity (mAh)	Dimension		Standard Charge		Rapid Charge		Weight Approx. (g)
				Diameter (mm)	Height (mm)	Current (ma)	Time(h)	Current (mA)	Time(h)	
	GT-1/3AAA17H	1.2	170	10.0±0.5	20.0±0.5	17	15	180	1.2	5
	GT-2/3AAA27H	1.2	270	10.0±0.5	28.5±0.5	27		270	1.2	8
	GT-AAA55H	1.2	550	10.0±0.5	44.0±0.5	55		550	1.2	13
	GT-5/4AAA65H	1.2	650	10.0±0.5	50.0±0.5	65		650	1.2	15
	GT-4/3AAA80H	1.2	800	10.0±0.5	65.0±0.5	80		800	1.2	18
	GT-5/3AAA100H	1.2	1000	10.0±0.5	80.0±0.5	100		1000	1.2	20
	GT-1/3AA27H	1.2	270	14.0±0.5	16.0±0.5	27		270	1.2	9
	GT-2/3AA60H	1.2	600	14.0±0.5	28.0±0.5	60		600	1.2	15
	GT-4/5AA110H	1.2	1100	14.0±0.5	43.0±0.5	110		1100	1.2	23
	GT-AA120H	1.2	1200	14.0±0.5	48.0±0.5	120		1200	1.2	26
	GT-2/3A90H	1.2	900	16.5±0.5	27.5±0.5	90		900	1.2	18
	GT-4/5A160H	1.2	1600	16.5±0.5	41.5±0.5	160		1600	1.2	29
	GT-A190H	1.2	1900	16.5±0.5	48.5±0.5	190		1900	1.2	35
	GT-SC180PH	1.2	1800	22.5±0.5	42.5±0.5	180		1800	1.2	50
	GT-SC240H	1.2	2400	22.5±0.5	42.5±0.5	240		2400	1.2	55
	GT-C320H	1.2	3200	22.5±0.5	49.3±0.5	320		3200	1.2	95
	GT-C350H	1.2	3500	25.5±0.5	49.3±0.5	350		3500	1.2	104
	GT-D900H	1.2	9000	32.5±0.5	60.0±0.5	900		4500	2.5	173
	GT-4/3D130H	1.2	13000	32.5±0.5	87.0±0.5	1300		6500	2.5	230

Note: High Cap, P:High Rate Discharge & Rapid Charge, T:High Temperature, Dimension:W

