

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GTM2065P65VV-F

May 9, 2024

GTM2065P65VV-F

Information

Model Number	GTM2065P65VV-F
Description	GTM2065P65VV-F, Medical Power Supply, Open Frame/Internal, Regulated Switchmode AC-DC Power Supply AC Adaptor, , Input Rating: 100-240V~, 50-60 Hz, Molex 26-60-4030 3 Position Header Pin 1: Line, Pin 2: Removed, PIN 3: Neutral, Output Rating: 65 Watts, Power rating with convection cooling (W) , 3.3-48V in 0.1V increments, Approvals: WEEE; Ukraine; EAC; VCCI; Book 60601; RoHS; China RoHS; Class I; CE; cRUus;
Model Picture	
Agency Documents	http://www.globtek.info/certs/GTM2065/
CE EC-Declaration	https://www.globtek.com/pdf/ec_declaration/a0O0c00000QD3lzEAD
RoHS/RoHS2 Declaration	https://www.globtek.com/pdf/rohs_cert/a0O0c00000QD3lzEAD
REACH Declaration	https://www.globtek.com/pdf/iso_certificates/REACH.pdf
Conflict Minerals Declaration	https://www.globtek.com/pdf/conflict-minerals.pdf

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GTM2065P65VV-F

May 9, 2024

MODEL PARAMETERS

Type	Open Frame/Internal
Technology	Regulated Switchmode AC-DC Power Supply AC Adaptor
Category	Medical Power Supply
Input Voltage	100-240V~, 50-60 Hz
I/P Amps (A)	1.5A
Wattage (W)	65.0
Vout Range (V)	3.3-48
Efficiency Level	
Ingress Protection	
Size (mm)	127*76.33*34.30

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.


<https://www.globtek.com/ds/2MTNnUSwHqcJruVhUmZVan.html>

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GTM2065P65VV-F

May 9, 2024

ENCLOSURE



PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

<https://www.globtek.com/ds/2MTNnUSwHqcJruVhUmZVan.html>

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GTM2065P65VV-F

May 9, 2024

RATING TABLE

Model Number	Voltage	Amps(A)	Watts(W)	RFQ
GTM2065P6524-F	24 V	2.7	64.80	RFQ

Model:GTM2065P65VV-F

May 9, 2024

SPECIFICATIONS

INPUT

INPUT VOLTAGE: 100Vac TO 240Vac

INPUT CURRENT: <1.5A rms AT 90VAC INPUT

INPUT FREQUENCY: 47HZ - 63HZ

POWER FACTOR: 0.7 TYPICAL AT 230 VAC FULL LOAD

OUTPUT :

OUTPUT VOLTAGE: 24 VDC

OUTPUT CURRENT: 2.7 A, NO LOAD TO FULL LOAD, NO MINIMUM LOAD REQUIRED

RATED OUTPUT POWER: 65 WATTS, MAXIMUM

OUTPUT REGULATION: +/- 2 % MEASURED AT THE OUTPUT CONNECTOR

LINE VOLTAGE REGULATION: +/- 0.5 % TYPICAL MEASURED AT FULL LOAD

HIGH FREQ. OUTPUT RIPPLE: 1% OF OUTPUT VOLTAGE , PEAK TO PEAK, TYPICAL AT NOMINAL LINE

TURN-ON/TURN-OFF OVERSHOOT: 5% MAXIMUM, 1mS TYPICAL RECOVERY TIME FOR 25% STEP LOAD

TURN-ON DELAY: 1 SECOND, TYPICAL AT 115 V INPUT VOLTAGE

HOLD-UP TIME:12 mS TYPICAL AT NOMINAL INPUT VOLTAGE AND FULL LOAD

INRUSH CURRENT: 20A TYPICAL AT 115Vac INPUT AND 40A TYPICAL AT 230Vac INPUT

SWITCHING FREQUENCY: 100KHZ TYPICAL, FIXED FREQUENCY

EFFICIENCY: 75% TYPICAL AT NOMINAL INPUT AND FULL LOAD

OUTPUT INDICATOR: GREEN LED FOR OUTPUT PRESENT

PROTECTION

OVER-VOLTAGE: VOLTAGE LIMITED TO LESS THAN 150%, CROWBAR METHOD

OVERLOAD: HICCUP MODE WITH AUTO-RECOVERY

SHORT CIRCUIT: HICCUP MODE, OUTPUT WILL AUTORECOVER UPON REMOVAL OF SHORT

INPUT PROTECTION: INPUT LINE FUSING

SAFETY APPROVALS: UL 60601 (THIRD EDITION), CUL TO 22.2 NO. 60601, DEMKO, CE

DIELECTRIC WITHSTAND VOLTAGE: 5656 Vdc FROM PRIMARY TO SECONDARY

EARTH LEAKAGE CURRENT: LESS THAN 300 uA at 240Vac INPUT VOLTAGE

EMI: COMPLIES WITH EN55022 CLASS B AND FCC PART 15 CLASS B, VCCI WHEN

TESTED WITH RESISTIVE LOAD, BOTH CONDUCTED AND RADIATED EMI.

CE MARK: TESTED TO COMPLY WITH EN61000-3-2 EN610003-3 AND EN50082-1

INCLUDING EN61000-4-2 , EN61000-4-3, EN61000-4-4,

EN61000-4-5, EN61000-4-6, EN61000-4-11

MTBF: 200,000 HOURS AT 25°C AMBIENT TEMPERATURE

OPERATING TEMPERATURE: 0°C TO 50°C AMBIENT TEMPERATURE

HUMIDITY: 0% TO 90% RELATIVE HUMIDITY

STORAGE TEMPERATURE - 40°C TO 80°C

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

<https://www.globtek.com/ds/2MTNnUSwHqcJruVhUmZVan.html>

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GTM2065P65VV-F

May 9, 2024

DERATING CURVE

Delivering leading edge, innovative power solutions for more than 30 years....



Model:GTM2065P65VV-F

May 9, 2024

INPUT CONFIGURATION

Description

Molex 26-60-4030 3 Position Header Pin 1: Line, Pin 2: Removed, PIN 3: Neutral



Optional Input Wiring Kits are available:

PN/Ordering No	Length	End A	End B
XHP410070M7MLX3(R)	70	JST XHP-4	Molex 09-93-0300
C810070M6MLX3(R)	60	IEC60320 C8	Molex 09-93-0300
C1410070M6MLX3(R)	60	IEC60320 C14	Molex 09-93-0300

Custom lengths, construction, cable types, ferrites, filters, and termination available upon request.

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GTM2065P65VV-F

May 9, 2024

Approvals

Logo	Description
	Attention Mark / Refer to operating manual for operating and service instructions
	60601-1 3rd Operating Instructions
	CE Certification
	CHINA SJ/T 11364-2014, China RoHS Chart: http://www.globtek.com/pdf/F-GT-DJD-8.4.1-006%20China%20RoHS%20Declaration%205-20-22.pdf
	cRUus UL Recognized Component E341350 3rd Edition w-RM ANSI-AAMI ES60601-1 (2005 + C1:09 + A2:10) and CAN-CSA-C22.2 No. 60601-1 (2008)
	Certification # TC RU AR46.B.69004 Custom Union of Russia, Belarus and Kazakhstan
	Indoor Use Only - Mark is on the label or Molded in the case
RoHS	Specifications of directive 2011/65/EU Annex VI (ROHS-2) with amendment 2015/863-EU (ROHS-3) http://www.ce-mark.com/Rohs%20final.pdf
	UKCA Certification
	Ukraine UKR Sepro (Document: www.globtek.com/html/iso_certificates/GT_Ukraine.pdf)
	Japan: Voluntary Control Council for Interference (VCCI)

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GTM2065P65VV-F

May 9, 2024



WEEE: Complies with EU 2012/19/EU (http://ec.europa.eu/environment/waste/weee/index_en.htm)
Mark is on the label or Molded in the case