

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-41052-WWVV-X.X-Q

September 21, 2024

**GT-41052-WWVV-X.X-Q**

**Information**

Model Number	GT-41052-WWVV-X.X-Q
Description	GT-41052-WWVV-X.X-Q, ICT/ITE Power Supply, Wall Plug-in, Regulated Switchmode AC-DC Power Supply AC Adaptor, , Input Rating: 100-240V~, 50-60 Hz, Blade Options for Q Series Wall Plug-in Power Supplies, Output Rating: 15 Watts, Power rating with convection cooling (W) , 5-48V in 0.1V increments, Approvals: South Africa; EAC; Morocco; UKCA; India BIS; CB 62368; RCM; NrCAN; Level IV; CE; Ukraine; RoHS; China RoHS; PSE; LPS 60950; Level V (24-48V); FCC; CB 60950; CCC; Double Insulation; WEEE; cULus; VCCI; Korea (5V Only); Korea (12V Only) pending; Level V ,24V& 1830/; SIQ; IP52; PSE; Korea (5.1V, 6V Only); PSE; PSE; PSE;
Model Picture	
Agency Documents	<a href="http://www.globtek.info/certs/GT-41052/">http://www.globtek.info/certs/GT-41052/</a>
CE EC-Declaration	<a href="https://www.globtek.com/pdf/ec_declaration/a0030000007P7YPEA0">https://www.globtek.com/pdf/ec_declaration/a0030000007P7YPEA0</a>
RoHS/RoHS2 Declaration	<a href="https://www.globtek.com/pdf/rohs_cert/a0030000007P7YPEA0">https://www.globtek.com/pdf/rohs_cert/a0030000007P7YPEA0</a>
REACH Declaration	<a href="https://www.globtek.com/pdf/iso_certificates/REACH.pdf">https://www.globtek.com/pdf/iso_certificates/REACH.pdf</a>
Conflict Minerals Declaration	<a href="https://www.globtek.com/pdf/conflict-minerals.pdf">https://www.globtek.com/pdf/conflict-minerals.pdf</a>

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-41052-WWVV-X.X-Q

September 21, 2024

**MODEL PARAMETERS**


Type	Wall Plug-in
Technology	Regulated Switchmode AC-DC Power Supply AC Adaptor
Category	ICT/ITE Power Supply
Input Voltage	100-240V~, 50-60 Hz
I/P Amps (A)	0.6 A
Wattage (W)	15.0
Vout Range (V)	5-48
Efficiency Level	V/IV see Approvals
Ingress Protection	IP52
Size (mm)	43.5* 74.0* 35.3

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-41052-WWVV-X.X-Q

September 21, 2024

# ENCLOSURE



Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-41052-WVVV-X.X-Q

September 21, 2024

**RATING TABLE**

Model Number	Voltage	Amps(A)	Watts(W)	RFQ
GT-41052-1305	5 V	2.6	13.00	<a href="#">RFQ</a>
GT-41052-1506	6 V	2.5	15.00	<a href="#">RFQ</a>
GT-41052-1507	7 V	2.143	15.00	<a href="#">RFQ</a>
GT-41052-1509-1.5	7.5 V	2	15.00	<a href="#">RFQ</a>
GT-41052-1509	9 V	1.666	14.99	<a href="#">RFQ</a>
GT-41052-1512	12 V	1.25	15.00	<a href="#">RFQ</a>
GT-41052-1515	15 V	1	15.00	<a href="#">RFQ</a>
GT-41052-1518	18 V	0.833	14.99	<a href="#">RFQ</a>
GT-41052-1520	20 V	0.84	16.80	<a href="#">RFQ</a>
GT-41052-1524	24 V	0.625	15.00	<a href="#">RFQ</a>
GT-41052-1548	48 V	0.312	14.98	<a href="#">RFQ</a>

## SPECIFICATIONS

### A) ELECTRICAL SPECIFICATIONS:

01. Input Voltage: Specified 90-264 Vac, Nameplate rated: 100-240Vac
02. Input Frequency: Specified 47-63 Hz, Nameplate rated 50-60Hz
03. Output Load Regulation: +/- 5% measured at the output connector
04. Line Voltage Regulation: +/- 1% typical measured at the output connector
05. Output Ripple (Vp-p): +/-1% or 150 mV whichever is greater at nominal output voltage, measured at 20 MHz bandwidth with 0.1 uf ceramic capacitor in parallel with 10 uf electrolytic capacitor connected at the end of the output connector
06. Turn-ON/OFF Overshoot: 5% maximum, 500uS max recovery time for 25% step load
07. Turn-ON Delay: 3000 mS, maximum
08. Hold-Up Time: 10 mS minimum at nominal input and full load
09. Inrush Current: 30A maximum at cold start 120VAC, 60A maximum cold start 230VAC
10. Switching Frequency: 66.5 KHz typical

### B) PROTECTION

01. Over-Voltage: Protected. Unit will auto recover upon removal of fault
02. Over current: Protected. Unit will auto recover upon removal of fault
03. Short Circuit: Protected. Unit will auto recover upon removal of fault
04. Input Protection: Input line fusing

### C) SAFETY

01. Dielectric Withstand Voltage: 4242Vdc from primary to secondary
02. Touch Current: <0.25mA @ 240Vac input voltage

### D) OTHER:

01. MTBF: 200,000 Hours @ 25°C ambient temperature
02. Operating Temperature: 0°C to 40°C ambient temperature
03. Humidity: 0% to 90% relative humidity
04. Storage Temperature: -10°C to 80°C
05. Cooling: Convection
06. RoHS 3: Complies with EU 2011/65/EU and China SJ/T 11363-2006

### E) ENCLOSURE

01. Housing: High impact plastic, 94V0 polycarbonate, non-vented
02. Size: 43.5 x 74.0 x 35.3+/-1.0 mm
03. Markings: Label and/or Pad Printed and/or Molded in the case

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-41052-WWVV-X.X-Q

September 21, 2024

## DERATING CURVE

---

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-41052-WWVV-X.X-Q


September 21, 2024

**INPUT CONFIGURATION**

Description Blade Options for Q Series Wall Plug-in Power Supplies

 Data Sheet: <http://en.globtek.com/interchangeable-blades.php>

 Insertion Instructions: <http://www.globtek.com/pdf/Instructions-Interchangeable-Blades.pdf>

 Video: [Q-Blade Style Instruction Video](#)


INPUT CONNECTOR: Q-Socket (below are available blades configurations which are "not included" (unless stated above); can be purchased separately, package with power supply or as a separate "Q-KIT" if specified

01. United States / Canada / Japan NEMA 1-15P/ IEC PLUG Type A [WORKS IN PLUG B] configuration: NA 2 blades, Class II; US/CA/JP P/N: Q-NA(R)
02. Australian AS 3112 configuration: SAA 2 blade/ IEC TYPE I, Class II; AU P/N: Q-SAA(R)
03. UK BS 1363 configuration: UK 3 blade with dummy Ground/ IEC TYPE G, Class II; GB P/N: Q-UK(R)
04. European CEE 7/16 configuration: Europlug 2 pins/ IEC TYPE C [WORKS IN TYPE E&F], Class II; EU P/N: Q-EU(R)
05. Korean KS C8305 configuration: 2 pins/SIMILAR TO IEC TYPE C, Class II; KR P/N: Q-KR(R)
06. Argentina IRAM 2073 configuration: 2 blades/SIMILAR TO IEC TYPE I; AR P/N: Class II Q-AR(R)
07. China GB 2099 configuration: 2 blades/SIMILAR TO TYPE A, Class II; CN P/N:Q-CN(R)
08. India IS 1293 6A/BS546 configuration: 5A, 3 pins with Dummy Ground, Class II/IEC TYPE D; IN P/N: Q-IN(R)
09. IEC60320/C18 Inlet, Class II; P/N: Q-C18(R)
10. Brazilian NBR6147 configuration: 2 pins, Class II;SIMILAR TO IEC TYPE C BR P/N: Q-BR(R)
11. South Africa SABS164-1 and India IS 1293, IS694, 16A type plug, 3 round prongs, Class II + dummy ground, IEC TYPE M P/N: Q-SANS164-1-16A(R)
12. South Africa SABS164-4, 3 round prongs with a notched prong @ 0°, Class II + dummy ground, IEC TYPE M Red, P/N: Q-SANS164-4C-16A(R)

**PROPRIETARY INFORMATION**

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

<https://www.globtek.com/ds/9HvjCGFL5TS/KxTZSRNG2qU.html>

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-41052-WWVV-X.X-Q

September 21, 2024

13. South Africa SABS164-4, 3 round prongs with a notched prong @ -53°, Class II + dummy ground, Blue, IEC TYPE M,  
P/N:

Q-SANS164-4L-16A(R)

14. South Africa SABS164-4, 3 round prongs with a notched prong @ +53°, Class II + dummy ground, Black,IEC TYPE M  
P/N:

Q-SANS164-4R-16A(R)

**Kits**

01. Q-KIT: 1,2,3,4 above

02. Q-KIT-INTL: 2,3,4 above

03. Q-KIT-6: 1,2,3,4,5,6 above

04. Q-KIT-7: 1,2,3,4,5,6,7 above

05. Q-KIT-8: 1,2,3,4,5,6,7,8 above




Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-41052-WWVV-X.X-Q

September 21, 2024

**OUTPUT CONFIGURATION**

Common output connector options:


 L Type (Coaxial  
5.5x2.5mm plug)

 C Type (Coaxial  
5.5x2.1mm plug)

 K Type (Coaxial  
3.5x1.3mm plug)

 LL Type (5.5x2.5mm  
Locking 760k type)

 CL Type (5.5x2.1mm  
Locking S761k type)

 ML2 Type (Molex  
housing 43025-0200)

 YL3 Type  
(KPPX-3P)


YL4 Type (KPPX-4P)


 EJ1/2/3/4/5 (EIAJ  
RC-5320A type  
connectors)

 MSB Type (Micro  
USB)

 USBC Type (USB  
Type C)

 Inquire for custom  
design

 For a comprehensive list of options, [click here](#)








Contact GlobTek for your specific requirements or custom solutions.

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-41052-WVVV-X.X-Q

September 21, 2024








## Approvals

Logo	Description
No Logo	CB Certificate IEC 60950-1:2005 (2nd Edition), Am 1: 2009, CB report IEC 60950-1:2005 (2nd Edition), Am 1: 2009 and EN 60950-1:2006 + Am 1:2010 + Am 11:2009 + Am 12:2011
No Logo Applicable	CB for IEC 62368-1:2014 (Second Edition)
 2000m	CCC to GB 17625.1-2022 ( Class A ) ;GB 4943.1-2022;GB/T 9254.1-2021
	CE Certification Class II CE Mark: tested to comply with EN55022:2006/A1:2007 Class B, EN610003-2, EN610003-3 including EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6N EN61000-4-1 EMI: Complies with EN55011 CLASS B and FCC Part 15 B
	CHINA SJ/T 11364-2014, China RoHS Chart: <a href="http://www.globtek.com/pdf/F-GT-DJD-8.4.1-006%20China%20RoHS%20Declaration%205-20-22">http://www.globtek.com/pdf/F-GT-DJD-8.4.1-006%20China%20RoHS%20Declaration%205-20-22</a>
	UL60950-1, cULus to UL 60950-1, 2nd Edition, 2007-03-27 and CSA C22.2 No. 60950-1-07, 2nd Edition, 2007-03
	
	Certification # TC RU AR46.B.69004 Custom Union of Russia, Belarus and Kazakhstan
	FCC PART 15 CLASS B

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-41052-WWVV-X.X-Q










September 21, 2024

	Bureau Of Indian Standards for GT-41052
	Indoor Use Only - Mark is on the label or Molded in the case
IP52	Ingress Protection: ?IP52 to IEC60529:2001 Protected against dust - limited ingress (no harmful deposit) and Protected against direct sprays up to 15 degrees from the vertical
 GlobTek, Inc.	JAPAN TUV R-PSE, Cert. No. JD 50314327, to J60950-1(H26) , J55022(H22),J3000(H25)[15V or less]. Please reference the following website for guidelines on PSE regulations: <a href="https://www.globtek.com/r2/Szj4Vb">https://www.globtek.com/r2/Szj4Vb</a>
 GlobTek, Inc.	JAPAN TUV R-PSE, Cert. No. JD 50471561.pdf, to J62368-1(H30) , J55032(H29), J3000(H25) ,[15V?30V]. Please reference the following website for PSE regulations: <a href="https://www.globtek.com/r2/Szj4Vb">https://www.globtek.com/r2/Szj4Vb</a>
 GlobTek, Inc.	JAPAN TUV R-PSE, Cert. No. JD 50471561, to J62368-1(H30) , J55032(H29), J3000(H25) ,[30V?60V]. Please reference the following website for PSE regulations: <a href="https://www.globtek.com/r2/Szj4Vb">https://www.globtek.com/r2/Szj4Vb</a>
 GlobTek, Inc.	JAPAN TUV R-PSE, Cert. No. JD 50471561, to J62368-1(H30) , J55032(H29), J3000(H25) ,[15V or less]. Please reference the following website for PSE regulations: <a href="https://www.globtek.com/r2/Szj4Vb">https://www.globtek.com/r2/Szj4Vb</a>
	Korea KET KC Mark GT-41052-1512 (7.512V only)
	Korea KET KC Mark GT-41052-1305 SU10109-6002 (5V Only)

Delivering leading edge, innovative power solutions for more than 30 years....

Model:GT-41052-WWVV-X.X-Q





September 21, 2024

 <p>직류전원장치 AC/DC ADAPTER KTC HU10499-15022A MSIP-REM-GSZ-GT-41052-1506 전기용품안전관리법에 의한 표시 최저소비효율기준 만족 제품 모델명:GT-41052-1506 Mfr. Name: GLOBTEK (SUZHOU) CO.,LTD A/S Center: 10-6221-6100</p>	<p>Korea KET KC Mark GT-41052-1506 HU10499-15022A (5.1V, 6V, 7v ONLY)</p>
<p><b>EFFICIENCY LEVEL</b> </p>	<p>Efficiency: complies to section 301 of Energy Independence and Security Act (EISA) complies with Energy Star tier 2 (North America), ECP tier 2 (China), MEPS tier 2 (Australia), Code of Conduct (Europe)</p>
<p><b>EFFICIENCY LEVEL</b> </p>	<p>Efficiency: complies to section 301 of Energy Independence and Security Act (EISA) complies with Energy Star tier 2 (North America), ECP tier 2 (China), MEPS tier 2 (Australia), Code of Conduct (Europe)... NOTE: 15V &amp; 1800 mm 20awg o/p cord only</p>
<p><b>EFFICIENCY LEVEL</b> </p>	<p>Efficiency: complies to section 301 of Energy Independence and Security Act (EISA) complies with Energy Star tier 2 (North America), ECP tier 2 (China), MEPS tier 2 (Australia), Code of Conduct (Europe)... NOTE: 24V &amp; 1830 mm 18awg o/p cord only</p>
<p>LPS</p>	<p>Limited Power Source 60950</p>
	<p>Morocco SDoC declaration <a href="http://www.globtek.info/certs/Morocco%20SDoC%20Declaration/">http://www.globtek.info/certs/Morocco%20SDoC%20Declaration/</a></p>
 EEV1191	<p>Natural Resources Canada (NRCAN): CSA Standard C381.1-08, QSP NRCAN EEV1191; <a href="http://shop.csa.ca/en/canada/energy-efficiency/canca-c3811-08/inv/27024802008">http://shop.csa.ca/en/canada/energy-efficiency/canca-c3811-08/inv/27024802008</a></p>
 GlobTek, Inc.	<p>JAPAN TUV Rheinland-PSE GlobTek Inc to J60950-1(H26) , J55022(H22),J3000(H25).Please fo the procedure listed in the following link for proper import to Japan: <a href="https://www.globtek.com/r2/Szj4Vb">https://www.globtek.com/r2/Szj4Vb</a></p>
 SAA-160017-EA	<p>RCM certificate SAA-160017-EA; Australia and New Zealand Regulatory Compliance, Mark ( <a href="http://rcm.standards.org.au/rcmfaq/rcmfaq.htm">http://rcm.standards.org.au/rcmfaq/rcmfaq.htm</a></p>
<p>RoHS</p>	<p>Specifications of directive 2011/65/EU Annex VI (ROHS-2) with amendment 2015/863-EU (ROHS <a href="http://www.ce-mark.com/Rohs%20final.pdf">http://www.ce-mark.com/Rohs%20final.pdf</a></p>
 IEC/EN60950-1	<p>SIQ Mark License Certificate EN 60950-1:2006 + Am 1:2010+ Am 11:2009 + Am 12:2011</p>

Delivering leading edge, innovative power solutions for more than **30** years....

Model:GT-41052-WWVV-X.X-Q

September 21, 2024

No Logo	South Africa approval NRCS
	UKCA Certification
 10276	Ukraine UKRSepto (Document: <a href="http://www.globtek.com/html/iso_certificates/GT_Ukraine.pdf">www.globtek.com/html/iso_certificates/GT_Ukraine.pdf</a> )
	Japan: Voluntary Control Council for Interference (VCCI)
	WEEE: Complies with EU 2012/19/EU ( <a href="http://ec.europa.eu/environment/waste/weee/index_en.htm">http://ec.europa.eu/environment/waste/weee/index_en.htm</a> ) Mark is on the label or Molded in the case