

Delivering leading edge, innovative power solutions for more than 30 years....

Model:DA-19.2-24G

April 28, 2024

DA-19.2-24G

Information

Model Number	DA-19.2-24G
Description	DA-19.2-24G, ICT/ITE Power Supply, Wall Plug-in, Regulated Linear AC-DC Power Supply AC Adaptor, , Input Rating: 115V~ / 60Hz, North America Blades with Ground Prong, Class I, (3) Conductors, Output Rating: 23.6 Watts, Power rating with convection cooling (W) , 24V in 0.1V increments, Approvals:
Model Picture	
Agency Documents	
CE EC-Declaration	https://www.globtek.com/pdf/ec_declaration/a0Oa000000FjHdvEAF
RoHS/RoHS2 Declaration	https://www.globtek.com/pdf/rohs_cert/a0Oa000000FjHdvEAF
REACH Declaration	https://www.globtek.com/pdf/iso_certificates/REACH.pdf
Conflict Minerals Declaration	https://www.globtek.com/pdf/conflict-minerals.pdf

Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

April 28, 2024

MODEL PARAMETERS

Type	Wall Plug-in
Technology	Regulated Linear AC-DC Power Supply AC Adaptor
Category	ICT/ITE Power Supply
Input Voltage	115V~ / 60Hz
I/P Amps (A)	
Wattage (W)	23.6
Vout Range (V)	24
Efficiency Level	USA DOE Level VI / Eco-design Directive 2009/125/EC, (EU) 2019/1782
Ingress Protection	
Size (mm)	

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

[n/a](#)

Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

April 28, 2024

ENCLOSURE

Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

April 28, 2024

RATING TABLE

Model Number	Voltage	Amps(A)	Watts(W)	RFQ
DA-16.2-15D-EI48	15 V	1	15.00	RFQ
DA-19.2-24G	24 V	0.8	19.20	RFQ

Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

April 28, 2024

SPECIFICATIONS

Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

April 28, 2024

DERATING CURVE

Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

April 28, 2024

INPUT CONFIGURATION

Description	North America Blades with Ground Prong, Class I, (3) Conductors
-------------	---

Model:DA-19.2-24G

April 28, 2024

OUTPUT CONFIGURATION

Common output connector options:



L Type (Coaxial
5.5x2.5mm plug)



C Type (Coaxial
5.5x2.1mm plug)



K Type (Coaxial
3.5x1.3mm plug)



LL Type (5.5x2.5mm
Locking 760k type)



CL Type (5.5x2.1mm
Locking S761k type)



ML2 Type (Molex
housing 43025-0200)



YL3 Type
(KPPX-3P)



YL4 Type (KPPX-4P)



EJ1/2/3/4/5 (EIAJ
RC-5320A type
connectors)



MSB Type (Micro
USB)



USBC Type (USB
Type C)



Inquire for custom
design

For a comprehensive list of options, [click here](#)

Contact GlobTek for your specific requirements or custom solutions.

Delivering leading edge, innovative power solutions for more than **30** years....

Model:DA-19.2-24G

April 28, 2024

Approvals

Logo	
------	--