http://www.globtek.com/iso-certificates.php

186 Veterans Dr, Northvale NJ 07647, USA 1-201-784-1000

Model:Create_Model	May 3, 202
Create_Model	
Information	
Model Number	Create_Model
Description	Create_Model, Medical/ICT/ITE/Household use Power Supply, Desktop/External, CREATE_TECHNOLOGY, , Input Rating: 100-240V~, 50-60Hz, , Output Rating: 1 Watts, Power rating with convection cooling (W) , ±60V in 0.1V increments, Approvals:
Model Picture	Create_Model
Agency Documents	
CE EC-Declaration	https://www.globtek.com/pdf/ec_declaration/a0Oa00000MFFHgEAP
RoHS/RoHS2 Declaration	https://www.globtek.com/pdf/rohs_cert/a0Oa00000MFFHgEAP
REACH Declaration	https://www.globtek.com/pdf/iso_certificates/REACH.pdf
Conflict Minerals Declaration	https://www.globtek.com/pdf/conflict-minerals.pdf

http://www.globtek.com/iso-certificates.php



186 Veterans Dr, Northvale NJ 07647, USA 1-201-784-1000

odel:Create_Model		May 3, 2
MODEL PARAMETERS		
Гуре	Desktop/External	
Technology	CREATE_TECHNOLOGY	
Category	Medical/ICT/ITE/Household use Power Supply	
nput Voltage	100-240V~, 50-60Hz	
/P Amps (A)	1	
Vattage (W)	1.0	
out Range (V)	±60	
Efficiency Level		
ngress Protection		
size (mm)		







186 Veterans Dr, Northvale NJ 07647, USA 1-201-784-1000

Model:Create Model

www.globtek.com

http://www.globtek.com/iso-certificates.php

May 3, 2024

ENCLOSURE	







™ GlobTek Inc.®

http://www.globtek.com/iso-certificates.php

el:Create_Model				May 3,
ATING TABLE				
lodel Number	Voltage	Amps(A)	Watts(W)	RFQ



www.globtek.com



186 Veterans Dr, Northvale NJ 07647, USA 1-201-784-1000

Model:Create_Model

http://www.globtek.com/iso-certificates.php

May 3, 2024

SPECIFICATIONS	







186 Veterans Dr, Northvale NJ 07647, USA 1-201-784-1000

http://www.globtek.com/iso-certificates.php

Model:Create_Model	May 3, 2024
DERATING CURVE	







186 Veterans Dr, Northvale NJ 07647, USA 1-201-784-1000

GlobTek Inc.®

http://www.globtek.com/iso-certificates.php

Model:Create_Model	May 3, 2024
INPUT CONFIGURATION	



http://www.globtek.com/iso-certificates.php

May 3, 2024

Delivering leading edge, innovative power solutions for more than 30 years....

OUTPUT CONFIGURATION

Common output connector options:



Model:Create Model





C Type (Coaxial 5.5x2.1mm plug)



K Type (Coaxial 3.5x1.3mm plug)



Locking 760k type)



LL Type (5.5x2.5mm CL Type (5.5x2.1mm Locking S761k type)



ML2 Type (Molex housing 43025-0200)



YL3 Type (KPPX-3P)



YL4 Type (KPPX-4P)



EJ1/2/3/4/5 (EIAJ RC-5320A type connectors)



MSB Type (Micro USB)



USBC Type (USB Type C)



Inquire for custom design

For a comprehensive list of options, click here

Contact GlobTek for your specific requirements or custom solutions.



www.globtek.com



186 Veterans Dr, Northvale NJ 07647, USA 1-201-784-1000

http://www.globtek.com/iso-certificates.php

odel:Create_Model	May 3, 202
Approvals	
Logo	