


PROPRIETARY INFORMATION:
 PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

REVISION			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE, RFS. 26974, RC	12/06/17	MK
B	CHANGE DESCRIPTION TO INDIA AND APPROVALS FROM SABS TO ISI, RFS. 27570, DH	09/08/20	MK




GENERAL SPECIFICATIONS:

RATING: 6A / 250V AC
 CABLE TYPE / SIZE: YY, 2 x 0.75 mm², FLAT
 TEMPERATURE RATING: 75°C
 CONDUCTOR COLORS: BLACK / RED
 CABLE JACKET COLOR: BLACK
 OVERALL LENGTH (L): 1800 ± 50 mm
 END 'A' PLUG: INDIA ISI:1293
 END 'B': IEC-320 / C7
 APPROVALS PLUG: INDIA BIS 'S' MARK
 APPROVALS CABLE: IS 694
 APPROVALS CONNECTOR: VDE, ENEC

PACKING:

HANKED
 L = 180±25 mm



NOTES:

1. CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).



2. PLUG MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).



DASH NO.	PART NO	REV.	DESCRIPTION	NOTES
TABULATION BLOCK				
		TOLERANCES: DECIMALS ANGULAR .xx +/- 0.1 +/- 1° .xxx +/- .005		GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 07647 www.globtek.com Tel. 201-784-1000 Fax 201.784.0111
		MILLIMETERS ANGULAR .xx +/- 0.3 +/- 1° .xxx +/- .013		
INIT.BY: RC	DATE: 12/06/17	DWG TITLE: INDIA DETACHABLED CORDSET		
DRAWN: NF	DATE: 12/06/17	FSCN No.: G, CC	SIZE: A	REV. B
APRVD: MK	DATE: 12/06/17	SCALE: NONE	PART NO: 2084111M8703B(R)	SHEET 1/1

Foot Note:
 Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL, CSA or EN Standards for proper installation instruction.

Limitation of Use:
 Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

Contents of this document are subject to change without prior notice