



## **GENERAL SPECIFICATIONS:**

RATING: 16A / 250V AC

CABLE TYPE / SIZE: H05VV-F, 3 x 1.5 mm<sup>2</sup>

TEMPERATURE RATING: 70° C

CONDUCTOR COLORS: BROWN / BLUE/ GREEN-YELLOW

CABLE JACKET COLOR: BLACK OVERALL LENGTH (L):  $2550 \pm 50 \text{ mm}$  CABLE OUTER DIAMETER:  $8.5 \pm 0.1 \text{ mm}$  END 'A' PLUG: CEE 7/7

END 'B': SEE TERMINATION TABLE

APPROVALS: VDE, N, D, FI, KEMA, OVE, CE, IMQ, S, USE, CEBEC

## **CONDUCTOR TERMINATION TABLE:**

Wire	Color	ROJ ± 5 mm	RIJ±1 mm	Terminal
Ground	Green-Yeloow	127	5	STRIPPED
Neutral	Blue	127	5	STRIPPED
Line	Brown	127	5	STRIPPED

## NOTES:

1. PLUG MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).



# PACKING:

BULK PACKED, BUNDLES OF 25.
MAXIMUM SHIPPING CARTON WEIGHT IS 30 KG.

		DASH NO.	PART NO	REV.	DESCRIPTION		NOTES		
			TABULATION BLOCK						
				TOLERANCES:  DECIMALS ANGULAR  .xx +/- 0.1 +/- 1*  .xxx +/005		www.globtek.com Tel. 201-784-1000 Fax			
Contents of this document are subject to change without prior notice	safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applica-	Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.	INIT.BY: EM	DATE: 03/13/09	MILLIMETE .xx +/- 0.3 .xxx +/01	+/- 1°	DWG TITLE: EUROPEAN NON-DETACHABLE POWER CO	ORD	
			DRAWN: NF	DATE: 03/13/09	FSCN No G, CC	.: SIZE		REV. A1	
			APRVD: HM	DATE: 03/13/09	SCALE: NONE		PART NO: 23144282M5001(R)	SHEET 1/1	