

REV

GENERAL SPECIFICATIONS:

RATING: 10A / 250V AC

CABLE TYPE / SIZE: SJT AWG 18X3 / H05VVF 3X1.0 mm²

TEMPERATURE RATING: 60° C

CONDUCTOR COLORS: BLUE / BROWN / GREEN-YELLOW

CABLE JACKET COLOR: BLACK OVERALL LENGTH (L): $1000 \pm 50 \text{ mm}$ CABLE OUTER DIAMETER: $8.3 \pm 0.2 \text{ mm}$ END 'A' PLUG; IEC 320 / C14 END 'B' IEC 320 / C13

APPROVALS PLUG: UL, CSA or cUL, VDE, N, S, D, FI, KEMA, SAA, UTE, CEBEC, OVE, IMQ,SEV APPROVALS CABLE: UL, CSA or cUL, VDE, N, S, D, FI, KEMA, SAA, SEV, CEBEC, OVE, IMQ

PROPRIETARY INFORMATION:

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR


USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY

APPROVALS CONNECTOR: UL, CSA or cUL, VDE, N, S, D, FI, BSI, KEMA, SEV, SAA, IMQ, UTE, CEBEC, OVE

NOTES:

1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).





Foot Note:
Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL,CSA or EN Standards for proper installation instruction.

Limitation of Use: Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.



REVISION

APPROVED

08/07/06

DESCRIPTION

INITIAL RELEASE, RFS, 9057, EM



PACKING:

 180 ± 20

HANKED

DASH NO.]	PART NO	REV.		DESCRIPTION	NOTES
TABULATION BLOCK						
			TOLE DECIMAI .xx +/- 0. .xxx +/0	1 +/- 1°	GlobTek, Inc. www.globtek.com 186 Veterans Dr. Nort Tel. 201-784-1000 F:	
INIT.BY:	EM	DATE: 08/07/06	MILLIMETE .xx +/- 0.3 .xxx +/01	+/- 1°	DWG TITLE: INTERNATIONAL JUMPER CORDSET	
DRAWN	INF	DATE: 08/07/06	FSCN No G, CC	.: SIZE		REV. A
APRVD: HM DATE: 08/07/06		SCALE: NONE		PART NO: 7055001M0701(R)	SHEET 1/1	