

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: USB A MALE 4 pin to USB MINI B MALE, GT Cable #UL 2725 AWG28 X 1P+AWG28 X 2C+AL + SHIELD BLACK PVC JACKET 3.8MM: SEE CODE / 4 + SHIELD Conductors, 3.8mm OD, UL 2725, 80°C Deg.C, V, -, Approvals: , 2000±100mm, GlobTek Black	
	Model No. Low voltage cable	
	Part No./Ordering No. USBA2M0MINIB(R)	Rev C1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification

ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at <https://www.globtek.com/iso-certificates/>
Prop 65 Statement:<https://en.globtek.com/prop-65-statement.pdf>

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (<https://en.globtek.com/terms-and-conditions/>).

The purchaser of this product (Customer) agrees that it is their sole responsibility to determine suitability/fitness of the product described in this specification for their application and to take precautions for protection against any hazards attendant to the handling and use of the product.

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.
Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing.
A delay in receipt of this form will delay delivery schedule.

Company Name:

Customer P/N:

Quote Number:

Date:

Authorized Representative Name:

Authorized Representative Signature:

RELEASED

By pudxc at 10:13 am, Apr 16, 2024

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc.
2015 - 2024
specC /04/16/2024 2:34:57 PM

Page 1 of 6

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: USB A MALE 4 pin to USB MINI B MALE, GT Cable #UL 2725 AWG28 X 1P+AWG28 X 2C+AL + SHIELD BLACK PVC JACKET 3.8MM: SEE CODE / 4 + SHIELD Conductors, 3.8mm OD, UL 2725, 80°C Deg.C, V, -, Approvals: , 2000±100mm, GlobTek Black		
	Model No. Low voltage cable		
	Part No./Ordering No. USBA2M0MINIB(R)		Rev C1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

REVISION HISTORY


REV	DESCRIPTION	SUB	DATE	APPROVED
C1	Update cable image, USB MINI B MALE dimension 7.5+/-0.3mm to 7.5+/-0.5mm	QA	04/15/2024	QA
C	Update spec to new format SF, change tolerance length to 2000±100 mm	QA	11/22/2021	QA
B	CLARIFY POLARITY TO INDUSTRY STANDARD, RFS. 25899, EM	QA	05/05/2015	QA
A	INITIAL RELEASE, RFS. 25772, BS	QA	01/08/2015	QA

Cordset Information:
CordsetColor:GlobTek Black
Cord Length (mm):2000±100

NOTES:


GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: USB A MALE 4 pin to USB MINI B MALE, GT Cable #UL 2725 AWG28 X 1P+AWG28 X 2C+AL + SHIELD BLACK PVC JACKET 3.8MM: SEE CODE / 4 + SHIELD Conductors, 3.8mm OD, UL 2725, 80°C Deg.C, V, -, Approvals: , 2000±100mm, GlobTek Black	
	Model No. Low voltage cable	
	Part No./Ordering No. USBA2M0MINIB(R)	Rev C1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE



GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: USB A MALE 4 pin to USB MINI B MALE, GT Cable #UL 2725 AWG28 X 1P+AWG28 X 2C+AL + SHIELD BLACK PVC JACKET 3.8MM: SEE CODE / 4 + SHIELD Conductors, 3.8mm OD, UL 2725, 80°C Deg.C, V, -, Approvals: , 2000±100mm, GlobTek Black	
	Model No. Low voltage cable	
	Part No./Ordering No. USBA2M0MINIB(R)	Rev C1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE



GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: USB A MALE 4 pin to USB MINI B MALE, GT Cable #UL 2725 AWG28 X 1P+AWG28 X 2C+AL + SHIELD BLACK PVC JACKET 3.8MM: SEE CODE / 4 + SHIELD Conductors, 3.8mm OD, UL 2725. 80°C Deg.C, V, -, Approvals: , 2000±100mm, GlobTek Black	
	Model No. Low voltage cable	
	Part No./Ordering No. USB A2M0MINIB(R)	Rev C1


CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

End A	Cable	End B
Code:USB A 4 pin	Code:UL 2725 AWG28 X 1P+AWG28 X 2C+AL + SHIELD	Code:USB MINI B
Description:USB A MALE 4 pin	BLACK PVC JACKET 3.8MM	Description:USB MINI B MALE
Rating (V):30	Description:GT Cable #UL 2725 AWG28 X 1P+AWG28 X	Rating (V):30
Rating (A):3,0	2C+AL + SHIELD BLACK PVC JACKET 3.8MM: SEE CODE /	Rating (A):3,0
Gender:Male	4 + SHIELD Conductors, 3.8mm OD, UL 2725, 80°C Deg.C, V,	Gender:Male
Overmolded:Yes	-, Approvals:	Overmolded:Yes
	Color:GlobTek Black	
	Wire Gauge(AWG):SEE CODE	
	Cond:4 + SHIELD	
	Type:UL 2725	
	Temperature:80°C° C	
	Amps:	
	Volts:	
	OD:3.8	
	ConductorsColors:-	
Overall cable rating:		
Plug Approvals	Cable Approvals	Connector Approvals
AGENCY ONLINE DOCUMENTS	http://www.globtek.info/certs/USB%20cables/	
RoHS/RoHS3 Declaration	https://www.globtek.com/pdf/rohs_cert/01ta00000054uoTAAQ	
REACH Declaration	https://www.globtek.com/pdf/iso_certificates/REACH.pdf	
Conflict Minerals Declaration	https://www.globtek.com/pdf/conflict-minerals.pdf	
Prop 65 Statement	https://en.globtek.com/prop-65-statement.pdf	
CE.UKCA.Cord	https://globtek.secure.force.com/spec/ec_decl_product_model_family_incl_cord?id=01ta00000054uoT	
IPXY rating is based on 3rd party testing and customers should check suitability and test system level IPXY rating before ordering.		

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: USB A MALE 4 pin to USB MINI B MALE, GT Cable #UL 2725 AWG28 X 1P+AWG28 X 2C+AL + SHIELD BLACK PVC JACKET 3.8MM: SEE CODE / 4 + SHIELD Conductors, 3.8mm OD, UL 2725, 80°C Deg.C, V, -, Approvals: , 2000±100mm, GlobTek Black	
	Model No. Low voltage cable	
	Part No./Ordering No. USBA2M0MINIB(R)	Rev C1

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

Hanking:USBA2M0MINIB(R) hanking
Description:
Image:



Notes/Modifications/Customizations (notes in this section supersede the values shown in the standard spec):

